

JUN 19 1999 Rec'd PCT/PTO 0 1 JUN 2001

FORM PTO-1390  
REV. 2/01

U. S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. 371ATTORNEY'S DOCKET NUMBER  
08364.0020U.S. APPLICATION NO.  
(If known, see 302 FR 1.5)

097/857291

INTERNATIONAL APPLICATION NO.

PCT/GB99/04014

INTERNATIONAL FILING DATE

December 1, 1999

PRIORITY DATE CLAIMED

December 1, 1998

TITLE OF INVENTION

A POLISHING MACHINE AND METHOD

APPLICANT(S) FOR DO/EO/US

Richard BINGHAM and David Charles RILEY

Applicant(s) herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.
4. ☐ The US has been elected by the expiration of 19 months from the priority date (Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c)(2)).
  - a. ☒ is attached hereto (required only if not communicated by the International Bureau).
  - b. ☐ has been communicated by the International Bureau.
  - c. ☐ is not required, as the application was filed with the United States Receiving Office (RO/US).
6. ☐ An English language translation of the International Application as filed (35 U.S.C. 371 (c)(2)).
  - a. ☐ is attached hereto.
  - b. ☐ has been previously submitted under 35 U.S.C. 154 (d)(4).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)).
  - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
  - b. ☐ have been communicated by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☒ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
10. ☐ An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 11 to 20 below concern document(s) or information included:

11. ☐ Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A **FIRST** preliminary amendment.
14. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
15. ☐ A Substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821-1.825.
18. ☐ A second copy of the published international application under 35 U.S.C. 154 (d)(4).
19. ☐ A second copy of the English language translation of the international application 35 U.S.C. 154 (d)(4).
20. ☒ Other items or information:
  - a. ☒ Copy of cover page of International Publication No. WO 00/32353
  - b. ☐ Copy of Notification of Missing Requirements.
  - c. ☐

09657291-082801

U.S. APPLICATION NO. (If known, see 37CFR 1.5)

INTERNATIONAL APPLICATION NO. PCT/GB99/04014

ATTORNEY'S DOCKET NUMBER  
08364.002021. ☒ The following fees are submitted:**BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)):**

Neither international preliminary examination fee (37 CFR 1.482)

nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO

and International Search Report not prepared by the EPO or JPO .....\$1000.00

International preliminary examination fee (37 CFR 1.482) not paid to

USPTO but International Search Report prepared by the EPO or JPO .....\$860.00

International preliminary examination fee (37 CFR 1.482) not paid to

USPTO but International Search fee (37 CFR 1.445(a)(2)) paid to USPTO .....\$710.00

International preliminary examination fee (37 CFR 1.482) paid to USPTO

but all claims did not satisfy provisions of PCT Article 33(1)-(4) .....\$690.00

International preliminary examination fee (37 CFR 1.482) paid to USPTO

and all claims satisfied provisions of PCT Article 33 (1)-(4) .....\$100.00

ENTER APPROPRIATE BASIC FEE AMOUNT =

Surcharge of \$130.00 for furnishing the oath or declaration later than  
months from the earliest claimed priority date (37 CFR 1.492 (e)).☐ 20 ☐ 30

CLAIMS

NUMBER FILED

NUMBER EXTRA

RATE

Total Claims

145

- 20 =

125

x \$18.00

Independent Claims

10

- 3 =

7

x \$80.00

MULTIPLE DEPENDENT CLAIM(S) (if applicable)

+\$270.00

TOTAL OF THE ABOVE CALCULATIONS =

☐ Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.

SUBTOTAL =

Processing fee of \$130.00 for furnishing the English translation later than  
months from the earliest priority date (37 CFR 1.492(f)).☐ 20 ☐ 30

TOTAL NATIONAL FEE =

Fee for recording the enclosed assignment (37 CFR 1.21 (h)). The assignment must be accompanied by  
an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property.

TOTAL FEES ENCLOSED =

Amount to be  
refunded:

charged

a. ☒ A check in the amount of \$ 3940.00 to cover the above fees is enclosed.b. ☐ Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \$ \_\_\_\_\_ to cover the above fees  
A duplicate copy of this sheet is enclosed.c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to  
Deposit Account No. 06-0916. A duplicate copy of this sheet is enclosed.d. ☐ Fees are to be charged to a credit card. **WARNING:** Information on this form may become public. **Credit card information  
should not be included on this form.** Provide credit card information and authorization on PTO-2038.NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b))  
must be filed and granted to restore the application to pending status.**SEND ALL CORRESPONDENCE TO:**Finnegan, Henderson, Farabow, Garrett & Dunner, L.L.P.  
1300 I Street, N.W.  
Washington, D.C. 20005-3315

DATED: June 1, 2001

SIGNATURE

Ernest F. Chapman, Reg. No. 25,961

NAME/REGISTRATION NO.

T03220 "T6245860

JC05 Rec'd PCT/PTO

0 1 JUN 2001

09/857291

JCO5 Rec'd PCT/PTO 01 JUN 2001

Attorney Docket No. 08364.0020

Customer Number: 22,852

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Application of )  
Richard BINGHAM et al. )  
Serial No.: Not Yet Assigned ) Group Art Unit: Not Assigned  
Filed: June 1, 2001 ) Examiner: Not Assigned  
National Phase Application of PCT/GB99/04014  
For: A POLISHING MACHINE AND METHOD

**Box PCT**  
**Assistant Commissioner for Patents**  
**Washington, D.C. 20231**  
Attention:

Sir:

**PRELIMINARY AMENDMENT**

Prior to examination, please amend the above-identified application as follows:

**IN THE CLAIMS:**

Please cancel claims 1-97 and substitute the following new claims 98-194 therefor:

98. (New) A machine for abrading or polishing a workpiece, the machine comprising:
- a holding surface for holding said workpiece;
  - a head member arranged along a rotation axis to rotate about the rotation axis;
  - a working member having a surface for abrading or polishing said workpiece arranged on said head member on said rotation axis for rotation about said rotation axis with said head member;
  - first driving means for driving said head member and said working member mounted thereon to rotate about said rotation axis;

head mounting means for mounting said head member;

second driving means for driving said head mounting means to incline said rotation axis of said head member relative to a precession axis intersecting said rotation axis, and for moving said head member to inclined positions with said rotation axis precessed about said precession axis; and

third driving means for relatively moving said head mounting means across said holding surface.

99. (New) A machine according to claim 98 wherein said first driving means is arranged to drive surface of said working member in a lateral direction relative to said holding surface, and said second driving means is adapted to rotate said surface of said working member relative to a position on said holding surface so that a direction of lateral relative movement of said surface of said working member and said holding surface rotate relative to said position on said holding surface.
100. (New) A machine according to claim 98, wherein said second driving means is arranged to move said head member to inclined positions distributed through an integer number of 360° of precession of said rotation axis about said precession axis.
101. (New) A machine according to claim 98, wherein said second driving means is arranged to move said head member in precession steps.
102. (New) A machine according to claim 101, wherein said second driving means is arranged to move said head member in precession steps which are symmetrically distributed about the precession axis through an integer number of 360° of angle of precession about the precession axis.

103. (New) A machine according to claim 98, wherein second driving means is arranged to incrementally carry out the precession at precession steps which are not integer division of 360 degrees.
104. (New) A machine according to claim 98, wherein said head mounting means is arranged such that said precession axis intersects said rotation axis at or near said abrasive member.
105. (New) A machine according to claim 98, including control means for controlling said first and second driving means such that the rate of movement of said head member about said rotation axis is substantially smaller than the rate of rotation of said head member.
106. (New) A machine according to claim 98, wherein said head mounting means includes first and second arcuate members arranged orthogonally, each with a center of curvature arranged to lie on an axis passing through or near said working member, said head member being mounted at a second end thereof to said first and second arcuate members by said second driving means to move said second end of said head member in a respective orthogonal arc about a respective axis of the arcuate members.
107. (New) A machine according to claim 98, wherein said third driving means is arranged to also relatively move said head member to and away from said holding surface.
108. (New) A machine according to claim 98, wherein said holding surface is arranged to be relatively rotated with respect to said head mounting means.
109. (New) A machine according to claim 98, wherein said working member is bulbous.

110. (New) A machine according to claim 109, wherein said working member is compliant.
111. (New) A machine according to claim 98, including control means operative to receive information on the topography of said workpiece and to control said second driving means to precess said head member about said precession axis normal to the surface of said workpiece at a position being abraded or polished.
112. (New) A machine according to claim 111, wherein said control means is operative to receive information on the roughness of said workpiece and a rate of removal for material removed from said workpiece by said working member, to control said third driving means to move said head mounting means in a repeated figuring pattern and to control said first, second and third driving means to remove less than four times a local roughness average for a region of the workpiece being polished or abraded during each configuring pattern.
113. (New) A machine according to claim 112, wherein said control means is adapted to control said second driving means to use varied inclined positions about said precession axis for each figuring pattern.
114. (New) A method of abrading or polishing the surface of a workpiece, the method comprising:  
mounting the workpiece on a holder;  
relatively inclining a head member arranged along a rotation axis and having a working member arranged axially on said rotation axis and on said head member with a surface for abrading or polishing the surface of said workpiece, so that said rotation axis is inclined relative to a precession axis intersecting said rotation axis,

said precession axis being normal to the surface of said workpiece at an area of contact of said surface of said working member;  
rotation said head member about said rotation axis;  
contacting said surface of said working member to said surface of said workpiece so that said surface of said working member moves in a direction laterally across said surface of said workpiece;  
moving the inclined head member to inclined positions rotated about said precession axis; and  
moving the incline head member to relatively move said working member and said surface of said workpiece in a figuring pattern.

115. (New) A method according to claim 114, wherein the step of moving the inclined head member to inclined positions rotated about said precession axis maintains an angle at which said head member is inclined relative to said precession axis substantially constant.
116. (New) A method according to claim 114, wherein said inclined head member is moved in said figuring pattern for each of a plurality of inclined positions rotated about said precession axis.
117. (New) A method according to claim 114, wherein said inclined positions rotated said precession axis are distributed through an integer number of rotations around said precession axis.
118. (New) A method according to claim 114, wherein said head member is moved in steps to said inclined positions rotated about said precession axis.

119. (New) A method according to claim 118, wherein said inclined positions are symmetrically distributed about said precession axis around an integer number of rotations about said precession axis.
120. (New) A method according to claim 118, wherein said inclined positions are not an integer division of 360 degrees of rotation about said precession axis.
121. (New) A method according to claim 114, wherein said precession axis intersects said rotation axis at or near said working member.
122. (New) A method according to claim 114, wherein the rate of movement of said head member about said precession axis is substantially smaller than the rate of rotation of said head member.
123. (New) A method according to claim 114, wherein said workpiece is relatively rotated with respect to said head member.
124. (New) A method according to claim 114, wherein said working member is bulbous.
125. (New) A method according to claim 124, wherein said working member is compliant and the position of said working member relative to said surface of said workpiece is controlled to control the area of contact between said surface of said workpiece and said working member.
126. (New) A method according to claim 114, wherein the movement of said head member is controlled in dependance upon information on the topology of said workpiece.
127. (New) A method according to claim 126, including receiving information on the roughness of said workpiece and a rate of removal for material removed from said workpiece by said working member, controlling the movement of said head



member to move in a repeated figuring pattern, and controlling the removal of material to remove less than four times a local roughness average for a region of the workpiece being polished or abraded during each figuring pattern.

128. (New) A method according to claim 127, wherein varied precession rotations of said head member are used for each figuring pattern.
129. (New) A machine for abrading and/or polishing a workpiece, the machine comprising:
- a holding surface for holding said workpiece;
  - a head carrying a face for abrading and/or polishing said workpiece;
  - a mechanical arrangement for supporting and moving said head across, to and from said holding surface;
  - a tilting mechanism mounted on said mechanical arrangement and arranged to tilt said head about a pivot to an angle relative to said holding surface; and
  - control means for controlling the position and tilt of said face of said head by controlling said mechanical arrangement and said tilting mechanism, said control means being operative to compensate for movement of said face when tilted by controlling said mechanical arrangement.
130. (New) A machine according to claim 129, wherein said control means is operative to perform the compensating control by calculating the change in position of said face caused by the tilt.
131. (New) A machine according to claim 129, wherein said control means is operative to perform the compensating control by looking-up the change in position of said face caused by the tilt.

132. (New) A method of abrading or polishing a workpiece, the method comprising:
- mounting the workpiece on a holder;
  - moving a head using a mechanical arrangement having a face for abrading or polishing said workpiece in a figuring pattern;
  - during the figuring, tilting said head about a pivot to an angle relative to said workpiece; and
  - controlling the position of said head in dependence upon the degree of tilt of said head so as to compensate for movement of said face relative to said workpiece caused by tilting said head.
133. (New) A method according to claim 132, wherein the movement of said face relative to said workpiece caused by tilting said head is calculated and used to control said mechanical arrangement.
134. (New) A method according to claim 132, wherein the movement of said face relative to said workpiece caused by tilting said head is looked-up using the angle of tilt and used to control said mechanical arrangement.
135. (New) A carrier medium storing instructions for controlling a processor to control a machine according to any one of claims 98 to 113 or 119 to 131.
136. (New) A tool for abrading or polishing a workpiece, the tool comprising:
- a bulbous compliant member;
  - a holder holding said compliant member so that the compliant member bulges there out of;

a membrane arranged over a surface of said compliant member to provide a working surface for abrading or polishing said workpiece;  
said membrane being flexible to follow the compliance of said compliant member; and  
a membrane carrier carrying said membrane and releasably attached to said holder to allow said membrane and said membrane carrier to be removed from said holder.

137. (New) A tool according to claim 136, wherein said membrane carrier is mechanically clamped to said holder.
138. (New) A tool according to claim 136, wherein said holder comprises a substantially cylindrical member, said compliant member is held at one end of the cylindrical member and said membrane carrier comprises a substantially cylindrical sleeve fitted over said cylindrical member.
139. (New) A tool according to claim 138, wherein said cylindrical member has an outer surface which tapers away from said compliant member and to which said cylindrical sleeve is clamped, and said cylindrical sleeve is shaped to deform to the taper of the outer surface of said cylindrical member.
140. (New) A tool according to claim 136, including means to allow said membrane and said surface of said compliant member to move relatively laterally.
141. (New) A tool according to claim 140, wherein said means comprises a lubricant or an unset adhesive.

142. (New) A tool according to claim 136, wherein said membrane has an abrasive material bonded thereto or impregnated therein.
143. (New) A tool according to claim 142, wherein said membrane is formed of a matrix material and a reinforcing material embedded in said matrix material.
144. (New) A tool according to claim 142, wherein said abrasive material is bonded to said membrane in discrete areas over said membrane.
145. (New) A tool according to claim 142, wherein said abrasive material is bonded to said membrane by epoxy or nickel.
146. (New) A tool according to claim 142, wherein said abrasive material is bound together and bonded to said membrane using a binder material containing an erosion promoter material to promote the erosion of the binder material during abrading or polishing to expose fresh abrasive material.
147. (New) A tool according to claim 142, wherein said abrasive material is bound together and bonded to said membrane using a binder material containing a lubricant material.
148. (New) A tool according to claim 136, wherein said compliant member comprises a volume of fluid and a flexible membrane covering at least in part said volume of fluid, and said volume of fluid is contained by said holder and said flexible membrane in combination and said flexible membrane is sealed to said holder.
149. (New) A tool according to claim 136, wherein said membrane comprises and adsorbent material for adsorbing abrasive material applied thereto for abrading or polishing said workpiece.

150. (New) A tool according to claim 149, wherein said membrane is formed of a cloth material.
151. (New) An abrasive cup for fitment to a tool for abrading or polishing a workpiece, the abrasive cup comprising:  
a sheet of flexible material having a shape for fitment to a corresponding bulbous compliant member of said tool, said sheet sufficiently flexible to flex during abrading; and  
a carrier carrying said sheet around a periphery of said sheet, said carrier having an arrangement for releasably fixing said abrasive cup to said tool.
152. (New) An abrasive cup according to claim 151, wherein said arrangement comprises a mechanical clamping arrangement.
153. (New) An abrasive cup according to claim 151, wherein said carrier comprises a sleeve for fitment to said tool, wherein said sheet is mounted at one end of said sleeve.
154. (New) An abrasive cup according to claim 153, wherein said sleeve is shaped to be radially deformable at a second end thereof.
155. (New) An abrasive cup according to claim 151, wherein said sheet has an abrasive material bonded thereto or impregnated therein for abrading or polishing said workpiece.
156. (New) An abrasive cup according to claim 155, wherein said sheet comprises a matrix material and a reinforcing material embedded in said matrix material.
157. (New) An abrasive cup according to claim 155, wherein said abrasive material is bonded to said sheet in discrete areas over said sheet.

158. (New) An abrasive cup according to claim 155, wherein said abrasive material is bonded to said sheet by epoxy or nickel.
159. (New) An abrasive cup according to claim 155, wherein said abrasive material is bound together and bonded to said sheet using a binder material containing an erosion promoter to promote the erosion of the binder material during abrading or polishing to expose fresh abrasive material.
160. (New) An abrasive cup according to claim 155, wherein said abrasive material is bound together and bonded to said sheet using a binder material containing a lubricant material.
161. (New) An abrasive cup according to claim 151, wherein said sheet comprises an adsorbent material for adsorbing abrasive material applied thereto for abrading or polishing said workpiece.
162. (New) An abrasive cup according to claim 161, wherein said sheet is formed of a cloth material.
163. (New) A method of forming an abrasive cup according to claim 151, the method comprising:  
forming said sheet of material over a carrier into a bulbous shape for fitment to a bulbous compliant member of said tool; and  
fixing said sheet to said carrier at a periphery of said sheet.
164. (New) The method of claim 163, wherein said forming step comprises applying said sheet to a forming tool, and forming said sheet to said bulbous shape.

165. (New) The method of claim 164, including a final step of pressing and/or heating said sheet.
166. (New) The method of claim 163, wherein said sheet comprises a substrate material and the method includes applying a flexible sheet on said substrate material for abrading or polishing said workpiece.
167. (New) A machine for abrading or polishing a workpiece, the machine comprising:  
a body extending along a rotation axis and having pressure transmission means at one end of said body, said body being rotatable about said rotation axis;  
a head releasably mounted on said end of said body, said head comprising a head housing, a head fluid pressure transmission means, and a resilient membrane forming a sealed head fluid chamber filled with fluid, said head fluid pressure transmission means being arranged in said head housing to cooperate with said pressure transmission means to transmit pressure to said head fluid chamber, and said resilient membrane being held at a periphery thereof by said head housing to extend bulbously therefrom for the application of pressure to said workpiece during abrading or polishing.
168. (New) A machine according to claim 167, wherein said body has a body fluid chamber filled with fluid terminating at said pressure transmission means.
169. (New) A machine according to claim 168, wherein said body fluid pressure transmission means and said head fluid pressure transmission means comprise respective displacement devices mounted respectively in said body and said head and coupled to one another when said head is mounted to said body.

170. (New) A machine according to claim 168, wherein said body fluid chamber and said head fluid chamber are filled with incompressible fluid.
171. (New) A machine according to claim 168, including fluid pressure control means comprising a passage from said body fluid chamber, to a fluid pressure control arrangement provided separate to said rotatable body.
172. (New) A machine according to claim 167, wherein said head is axially mountable to said body.
173. (New) A tool head for releasably mounting on a tool body of a machine for abrading or polishing a workpiece, the tool body having pressure transmission means, the tool head comprising:
- a head housing, a head fluid pressure transmission means and a resilient membrane forming a sealed head fluid chamber for holding fluid, said head fluid pressure transmission means being arranged in said head housing to allow the coupling of fluid pressure in said head fluid chamber to said pressure transmission means, and said resilient membrane being held at a periphery thereof by said head housing to extend bulbously therefrom for the application of pressure to said workpiece during abrading or polishing.
174. (New) A tool head according to claim 173, wherein said head fluid transmission means comprises a displacement device for coupling with said pressure transmission means comprising a displacement device when said tool head is mounted on said tool body.



175. (New) A tool head according to claim 173, wherein said head fluid chamber is filled with incompressible fluid.

176. (New) A method of controlling polishing or abrading of a workpiece, the method comprising:

receiving data defining an influence function of a tool, the influence function

defining the pattern of removal of material from the workpiece for a

predetermined dwell time or speed of said tool;

receiving data on a desired profile and a current profile of a surface of said workpiece;

determining the difference between the desired profile and the current profile to determine a target removal profile;

determining dwell times or tool speeds for predetermined positions on said surface of said workpiece to provide a predicted removal profile by performing a numerical optimization of the dwell times or tool speeds for the predetermined positions using the influence function to reduce at least one cost function; and

controlling the polishing or abrading of said workpiece using the determined dwell times.

177. (New) A method according to claim 176, wherein said numerical optimization comprises determining a set of dwell times or tool speeds for the predetermined positions which have a minimum value for a difference between said target removal profile and said predicted removal profile.

178. (New) A method according to claim 176, wherein said numerical optimization comprises a genetic algorithm, wherein values for the dwell times or tool speeds comprise a gene pool for the algorithm.
179. (New) A method according to claim 176, wherein said desired profile comprises a desired radial profile for a circular workpiece, said influence function is defined as a 2D function, and the predetermined positions comprise radial positions across said surface of said workpiece.
180. (New) A method according to claim 176, wherein said desired profile comprises a desired 3D profile, said influence function is defined as a 3D function, and the determined positions comprise a 2D array of positions across said surface of said workpiece.
181. (New) A method according to claim 176, wherein said cost function for predetermined dwell times or tool speed is the sum of squares of the errors between the target removal profile and the predicted removal profile obtained using the predetermined dwell times.
182. (New) A method according to claim 176, wherein said numerical optimization iteratively searches for the best dwell times or tool speeds for said predetermined positions to substantially achieve the desired profile.
183. (New) A method according to claim 176, including measuring a profile of said workpiece after polishing, comparing the measured profile with said current profile before polishing to determine a measured removal profile, determining dwell times or tool speeds expected to achieve said measured removal profile using said

numerical optimization, determining at least one correction factor for dwell times or tool speeds using the dwell times or tool speeds used to polish said workpiece and the dwell times or tool speeds expected to achieve said measures removal profile, and applying said at least one correction factor to dwell times or tool speeds used in future polishing of said workpiece.

184. (New) Apparatus for abrading or polishing a workpiece, the apparatus comprising:
- first inputting means for inputting data defining an influence function of a too, the influence function defining the pattern of removal of material from the workpiece for a predetermined dwell time or speed of said tool;
  - second inputting means for inputting data on a desired profile and a current profile of a surface or said workpiece;
  - first determining means for determining a target removal profile from the difference between the desired profile and the current profile;
  - second determining means for determining dwell times or tool speeds for predetermined positions on said surface of said workpiece to provide a predicted removal profile by performing a numerical optimization of the dwell times or tool speeds for the predetermined positions using the influence function to reduce at least one cost function; and
  - control means for controlling the polishing or abrading of said workpiece using said tool an the determined dwell times or tool speeds.
185. (New) Apparatus according to claim 184, wherein said second determining means is adapted to determine a set of dwell times or tool speeds which have a minimum

value for a difference between said target removal profile and said predicted removal profile.

186. (New) Apparatus according to claim 184, wherein said second determining means is adapted to carry out a genetic algorithm, wherein values for the dwell times or tool speeds for the predetermined positions comprise a gene pool for the algorithm.
187. (New) Apparatus according to claim 184, wherein said second inputting means is adapted to input said desired profile as a desired radial profile for a circular workpiece, said first inputting means is adapted to input said influence function as a 2D function, and said second determining means is adapted to determine said dwell times or tool speeds for radial positions across said surface of said workpiece.
188. (New) Apparatus according to claim 184, wherein said second inputting means is adapted to input said desired profile as a 3D profile, said first inputting means is adapted to input said influence function as a 3D function, and said second determining means is adapted to determine said dwell times or tool speeds for a 2D array of positions across said surface of said workpiece.
189. (New) Apparatus according to claim 184, wherein said second determining means is adapted to determine said dwell times or tool speeds using a said cost function for determined dwell times or tool speeds comprising the sum of the squares of the errors between the target removal profile and the predicted removal profile obtained using the determined dwell times or tool speeds.

190. (New) Apparatus according to claim 184, wherein said second determining means is adapted to perform said numerical optimization iteratively to search for the best dwell times or tool speeds for said predetermined positions to substantially achieve the desired profile.
191. (New) Apparatus according to claim 184, including measuring means for measuring a profile of said workpiece after polishing, comparing means for comparing the measured profile with said current profile before polishing to determine a measured removal profile, third determining means for determining dwell times or tool speeds expected to achieve said measured removal profile, fourth determining means for determining at least one correction factor for dwell times or tool speeds using the dwell time or tool speeds expected to achieve said measured removal profile and the dwell times or tools speeds used to polish said workpiece, and correction means for applying said at least one correction factor to dwell times or tool speeds used in future polishing or said workpiece.
192. (New) A computer program for controlling a computer to carry out the method of claim 176.
193. (New) A carrier medium carrying the computer program according to claim 192.
194. (New) A method of manufacturing a device comprising the method of any one of claims 114 to 123, 132 to 134 or 176 to 183.

**REMARKS**

The amendment is fully supported by the Specification and drawings, will not require an additional search, and does not raise new issues. Therefore, applicant respectfully requests that this Preliminary Amendment be entered and the requested changes made.


The examiner is respectfully requested to consider the above preliminary amendment prior to examination of the application.

If there are any fees due in connection with the filing of this preliminary amendment, please charge the fees to Deposit Account No. 06-0916. If a fee is required for an extension of time under 37 C.F.R. § 1.136 not accounted for above, such an extension is requested and the fee should also be charged to our deposit account.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,  
GARRETT & DUNNER, L.L.P.

By:

  
Ernest F. Chapman  
Reg. No. 25,961

Dated: June 1, 2001  
EFC/FPD/mld  
Enclosures

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of )  
Richard BINGHAM et al. )  
Serial No.: 09/857,291 ) Group Art Unit:  
Filed: June 1, 2001 ) Examiner:  
National Phase Application of PCT/GB99/04014

For: A POLISHING MACHINE AND METHOD

Assistant Commissioner for Patents  
Washington, D.C. 20231  
Attention:

Sir:

**SECOND PRELIMINARY AMENDMENT**

Prior to examination, please amend the above-identified application as follows:

**IN THE CLAIMS:**

Please amend claim 135 as follows:

135. (Amended) A carrier medium storing instructions for controlling a processor to control a machine according to any one of claims 98 to 113 or 129 to 131.

**REMARKS**

The amendment is fully supported by the Specification and drawings, will not require an additional search, and does not raise new issues. Therefore, applicant respectfully requests that this Preliminary Amendment be entered and the requested changes made.

An amended version of claim 135 is attached for the Examiner's convenience pursuant to new rule 37 C.F.R. 1.121 (c)(1)(ii).

09/857,291 - 0001

LAW OFFICES


FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N.W.  
WASHINGTON, DC 20005  
202-408-4000

The examiner is respectfully requested to consider the above preliminary amendment prior to examination of the application.

If there are any fees due in connection with the filing of this preliminary amendment, please charge the fees to Deposit Account No. 06-0916. If a fee is required for an extension of time under 37 C.F.R. § 1.136 not accounted for above, such an extension is requested and the fee should also be charged to our deposit account.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,  
GARRETT & DUNNER, L.L.P.

By:   
Ernest F. Chapman  
Reg. No. 25,961

Dated: August 28, 2001  
EFC/FPD/mld  
Enclosures

09857291.082801

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000



**APPENDIX TO THE PRELIMINARY AMENDMENT**

Please amend claim 135 as follows:

135. (Amended) A carrier medium storing instructions for controlling a processor  
to control a machine according to any one of claims 98 to 113 or  
[119] 129 to 131.

08364.0020 June 1, 2001

WO 00/32353

27/PRTS

09/857291  
JC05 Rec'd PCT/PTO 01 JUN 2001  
PCT/GB99/04014

1

## A POLISHING MACHINE AND METHOD

The present invention generally relates to a polishing machine and method for abrading or polishing a workpiece.

The present invention also relates to a tool and an abrasive cup for fitment to a tool for the use in abrading or polishing a workpiece.

The abrading or polishing of the surface of a workpiece is a technique which has applications in many different fields including the production of semi-conductor devices and optical components. The requirement is to provide a surface which has a particular surface contour and a particular surface finish i.e. smoothness. In the field of optical polishing there are two different techniques, one technique uses a tool for polishing which has a size comparable with that of the size of the workpiece. The limitation of this technique is that the tool is designed for a specific workpiece and this cannot be used universally. In order to reduce this limitation, an active lap has been developed as disclosed in GB 2163076 wherein the pressure distribution over the workpiece can be varied in order to differentially abrade or polish.

In the second technique the tool is substantially

WO 00/32353

PCT/GB99/04014

2

smaller than the workpiece and is moved across the workpiece in order to carry out the abrading or polishing process. Such a technique is described in US 4128968. In this technique two pads are maintained in contact with the surface of the workpiece and are relatively rotated and moved in a spiralling path around the surface of the workpiece. Another such technique disclosed in WO97/00155 uses a tool which has a flexible working surface so that the effective area of contact with the workpiece can be controlled. This provides the benefit that the area being polished at any one time during the polishing cycle can be controlled.

In these prior art techniques, the tool is usually spun around an axis normal to the workpiece. A limitation to this technique is that on the axis the relative movement is zero and thus the removal or ablation rate is zero. Thus the use of such a tool having such a removal profile makes it difficult to achieve a desired target profile using an automatic polishing or abrading technique.

In the technique of WO97/00155, the angle of attack of the tool to the workpiece is variable using an arrangement which provides a "virtual pivot" on the surface of the workpiece. This has the benefit of ensuring when the tool is tilted there is no lateral or

T02230" T627291 09257291

WO 00/32353

PCT/GB99/04014

3

vertical movement of the centre of the tool in contact with the workpiece. However, the disclosed mechanical arrangement is complex and large.

US patent number 4958463 discloses a different technique in which a resilient working member is rotated about its axis parallel to the surface of the workpiece to provide relative lateral motion between the working member and the surface of the workpiece. The working member is held to rotate in a mounting member. The mounting member mounting the working member is also rotated perpendicularly to the surface of the workpiece. While this technique does not suffer from the lack of removal of material in the centre of the area of contact, it requires a complex arrangement involving the use of two motors to provide the two axes of rotation.

In accordance with a first aspect of the present invention there is provided a method and apparatus for abrading or polishing a workpiece. A workpiece is held on a holding surface of the machine and a head having a surface for abrading or polishing the workpiece is moved across the workpiece in a figuring pattern in order to polish or abrade the workpiece. In addition to the figuring movement of the head, the face of the head carrying out the abrading or polishing is arranged to move in a direction laterally on the surface of the

WO 00/32353

PCT/GB99/04014

4

workpiece by inclining and rotating the head. The direction of lateral movement of the face is rotated by moving the head to positions which are a precession of the inclined head about a precession axis normal to the  
5 workpiece surface.

Thus in accordance with this aspect of the present invention, instead of having a removal profile which is zero at the centre of the area of contact of the tool, it is possible to simply incline the head to use a face  
10 which is moved laterally relative to the workpiece, thus providing a non-axially symmetric removal profile at any one instance in time. An axially symmetric removal profile is however an advantage when deterministic automatic polishing is required. In order to make the  
15 average removal profile over a period of time symmetric, the head is moved to positions precessed relative to the surface of the workpiece such that the direction of lateral relative movement of the face of the tool rotates. Thus any pattern generated in the surface of the  
20 workpiece by the lateral movement at an instance in time will be generated at a number of rotational angles thus reducing the defects and producing an axially symmetric profile.

Another advantage of the technique of this aspect of  
25 the invention is that the movement of the abrading face

09857291.082801

WO 00/32353

PCT/GB99/04014

5

is self-wetting. The cooling/lubricating fluid or slurry used between the abrading surface and the workpiece will be carried under the tool by the polishing action. In contrast, in the prior art techniques which use axial rotation of a tool normal to the surface of the workpiece, the cooling/lubricating fluid will tend to move to the circumference of the polishing area by centrifugal force.

This aspect of the present invention is applicable to any form of inclined rotating tool which can provide relative lateral movement between the workpiece and the abrading face and which can be precessed to rotate the direction of lateral movement e.g. an axially rotatable conical shaped tool.

In order to achieve averaging, preferably the precession takes place throughout at least 360 degrees. This can be achieved by incrementing the precession. Preferably such increments should be over more than one precession cycle. In one embodiment the increment in the precession is not an integer division of 360 degrees so that the direction of relative lateral motion is different for each cycle. In another embodiment the increments are symmetric about the 360° precession cycle.

In a preferred embodiment, the face comprises a compliant bulbous portion extending from the head. As

00857291.08301  
T03280"16225860

WO 00/32353

PCT/GB99/04014

6

the compliant portion is rotated about its inclined axis  
the bulbous portion forms an area of contact with the  
workpiece wherein there is relative lateral movement.

The abrading face can comprise a cloth or pitch on  
to which an abraded loaded slurry e.g. a diamond paste is  
placed. Alternatively, a bound abrasive can be used  
which is bound to the abrading face. When such a bound  
abrasive is used, only a cooling/lubricating fluid is  
required.

A second aspect of the present invention provides a  
polishing or abrading machine or method wherein a head  
carrying a face for abrading or polishing is held by a  
mechanical arrangement to allow for figuring of a  
workpiece. The mechanical arrangement includes a tilting  
mechanism arranged to tilt the head about a pivot to  
enable tilting relative to the workpiece. In this way not  
only can the head follow the contours of the workpiece  
but also it can be tilted to either follow the surface or  
be inclined at a required angle to the surface. Because  
the pivot is not on the workpiece when the head is tilted  
there is a displacement of the face of the head across,  
to or away from the workpiece. This is compensated for  
by either calculating or looking-up the required  
compensation values to control the mechanical arrangement

WO 00/32353

PCT/GB99/04014

7

to take up the displacements in the lateral and vertical directions.

This aspect of this present invention differs from the prior art disclosed in WO97/00155 in that a far simpler pivoting arrangement can be provided for example by use of an orthogonal arcuate track arrangement allowing tilting in any solid angle. In order to enable the use of a such a simple pivoting arrangement however, the displacement of the polishing face must be compensated for by a controller which determines the solid tilt angle and compensates the lateral and vertical displacements accordingly. Further, even if the virtual pivot is used as disclosed in WO97/00155, if a soft face is used e.g. a compliant material, it is necessary to compensate for the displacement of the compliant material as the head is pressed onto the workpiece.

Either the first aspect or the second aspect of the present invention can be implemented using a polishing apparatus under computer control. These aspects of the present invention can thus be embodied as a computer program and a carrier medium storing the computer program for controlling a processor to control the polishing apparatus. Since the computer program can be transmitted over a network such as the Internet, these aspects of the present invention can be embodied as a signal carrying



WO 00/32353

PCT/GB99/04014

8

the computer program for controlling the processor to control a polishing or abrading apparatus.

5 A third aspect of the present invention provides an improvement to the soft tool of WO97/00155. The soft tool is provided with an abrasive cup for releasable fitment to the soft tool wherein a sheet is preformed in the shape of the surface of the soft tool to be used for polishing and is sufficiently flexible to allow its deformation as a result of compression of the soft tool during abrading or polishing. The sheet is held at its periphery by a carrier member which is releasably mountable to a holder of the soft tool.

10 Since the sheet will become worn during the polishing or abrading process, it is removable from the tool. Since the surface of the tool to be used for polishing is compliant, the membrane must be flexible to conform to any compliance of the flexible tool.

15 Because of the compliance of the soft tool and the need for the sheet to flex to follow the compliance, it is preferred that means are provided to allow relative lateral movement between the sheet and the surface of the compliant tool. This is necessary in view of the different radii of curvature of the surface of the soft tool and of the sheet. Suitable means which can allow

T08280" T6275860

WO 00/32353

PCT/GB99/04014

9

for some relative lateral movement comprises a lubricant or an unset adhesive. Use of an unset adhesive provides the advantage that the sheet is adhered to the surface of the soft tool and thus benefits from the support provided thereby. In other words during the abrading or polishing operation some of the lateral force experienced by the sheet can be passed to the soft tool. If on the other hand a lubricant is used, the sheet must have sufficient torsional strength to be able to withstand the forces experienced during the abrading or polishing operation as the tool is dragged across the surface of the workpiece since the sheet is mechanically driven from its periphery.

A fourth aspect of the present invention provides a method and a machine for abrading or polishing a workpiece and which has a soft tool head comprising a fluid filled chamber which is detachable from a tool body without having to break the fluid seal. The tool body is a rotational body which extends along the rotational axis and has a pressure transmission means at one end thereof for transmitting pressure to the fluid chamber of the tool head. The tool head is releasably mounted on the tool body and comprises a head housing, a head fluid transmission means and resilient membrane forming the

WO 00/32353

PCT/GB99/04014

10

5 seal fluid chamber. The head fluid pressure transmission means is arranged to cooperate with the pressure transmission means of the tool body to transmit pressure to the fluid in the head of fluid chamber. The resilient membrane is held at its periphery by the head housing to extend in a curved manner therefrom for the application of pressure to the workpiece during abrading or polishing.

10 This aspect of the present invention provides a resilient working member, the resilience of which can be controlled by controlling the pressure of the fluid within it. The tool head benefiting from this advantage can also be readily interchanged when necessary due to wear or due to the need to change to different tool head sizes.

15 In one embodiment of the present invention, the tool body has a fluid chamber filled with fluid terminating at the pressure transmission means. This enables fluid pressure to be transmitted through the fluid body chamber to the head body chamber from a fluid pressure control arrangement provided separately into the rotatable tool. Because two separate fluid filled chambers are used in the tool head and the tool body, the tool head can be readily removed from the tool body without breaking the fluid seal.

20

25

09857291.082801

WO 00/32353

PCT/GB99/04014

11

In one embodiment the fluid pressure is transmitted from the body fluid chamber to the head fluid chamber via respective displacement devices mounted on the tool body and the tool head respectively. The respective displacement devices are coupled to one another to provide the transmission of pressure. This may be a direct physical coupling or a coupling via an intermediary e.g. via air.

A fifth aspect of the present invention provides a method and apparatus for controlling polishing or abrading of a workpiece. Data defining an influence function of the tool is used. The influence function defines the pattern of removal of material from the workpiece for a predetermined dwell time or speed of the tool. The desired profile is compared with the current profile of the surface to the workpiece and a difference between them is determined. Dwell times or tool speeds for predetermined positions on the surface of the workpiece are determined using numerical optimisation of the dwell times or tool speeds for the predetermined positions using the influence function to reduce a cost function.

The technique is preferably iterative wherein a cost function is repeatedly determined for various dwell times

WO 00/32353

PCT/GB99/04014

12

or tool speeds until a minimum cost function is found relating to the optimum dwell times or tool speeds to substantially achieve the desired profile.

Thus for this technique, predetermined positions are used for the application of the influence functions and the technique thus becomes simply the optimisation of a set of values to achieve a result.

There are many techniques which can be used for this type of optimisation. The technique can reduce the sum of the squares of the difference between the target removal profile and a predicted removal profile. A genetic algorithm can be used in order to determine candidate values for the dwell times or tool speeds. A cost function can be calculated for the dwell times or tool speeds to determine whether the proposed value is a candidate for keeping in the "gene" pool, or not.

In one embodiment, the desired profile comprises a desired radial profile for a circular workpiece and is thus only a two dimensional profile. This radial function applies equally to all radii of the surface of the workpiece. The influence function is also defined as a two dimensional function and the predetermined positions comprise radial positions across the surface of the workpiece. Thus the numerical optimisation technique only comprises the optimisation of a sequence of numbers

WO 00/32353

PCT/GB99/04014

13

defining the dwell times for radial positions across the surface of the workpiece, having regard to the radial error in the profile achieved.

In a more complex embodiment of the present invention, the desired profile is defined across an area of the surface of the workpiece and thus comprises a three dimensional profile. The influence function is thus also necessarily defined as a three dimensional function or at least a projection of a two dimensional radial function into three dimensions. The predetermined positions at which the influence function is to be applied comprise a two dimensional array of positions across the surface of the workpiece. Thus in this embodiment of the present invention, the numerical analysis technique must determine dwell times or tool speeds for the two dimensional array of positions across the surface of the workpiece. In order to reduce computational time, it is possible to use a coarse grid of array positions in order to determine the dwell times or tool speeds for the positions. Dwell times or tool speeds for intermediate positions can then be determined by interpolation where necessary. For example, when the figuring pattern to be traced out by the head comprises a circular pattern, the interpolation takes place in order to define dwell times or tool speeds along arcs to

WO 00/32353

PCT/GB99/04014

14

be traced by the head. Where the figuring pattern is to comprise a rastering scan, the interpolation is carried out for the linear rastering pattern in order to determine dwell times or tool speeds along the path to be taken by the head during the figuring operation.

Embodiments of the present invention will now be described with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a polishing apparatus using a soft tool in accordance with an embodiment of the present invention,

Figure 2 is a view of part of the polishing apparatus of Figure 1 showing the turntable and the Z axis movement arrangement in more detail,

Figure 3 is a view of part of the polishing apparatus of Figure 1, showing the arcuate track arrangements for providing the precession of the head,

Figure 4 is a sectional diagram through the head of the polishing apparatus of Figure 1,

Figure 5 is a part sectional view showing in more detail the junction between the rotating part of the head and the stationary part of the head,

Figure 6 is a perspective view of the spoked member within the head,

WO 00/32353

PCT/GB99/04014

15

Figure 7 is a sectional view of an alternative tool body fitted with a small tool head,

Figure 8 is another view of the tool body of Figure 7 showing a large tool head for fitment thereto,

5        Figure 9 is a view showing the fitment of an abrasive cup to the tool head,

Figure 10 is a diagram of the sheet material used in the construction of the abrasive cup,

10        Figure 11 is a diagram of an abrasive sheet material optionally used in addition to the sheet material of Figure 10 on the abrasive cup,

Figure 12 is a series of diagrams illustrating the operations carried out during the manufacture of the abrasive cup,

15        Figure 13 is a flow diagram showing the steps of manufacturing the abrasive cup.

Figure 14a schematically illustrates the prior art method of polishing using the soft tool,

20        Figure 14b is a graph illustrating the removal profile of the soft tool used in accordance with the prior art method and used in accordance with the present embodiment,

Figure 14c illustrates the method of using the soft tool in this embodiment,

25        Figure 15 is a diagram illustrating the pattern of

T08280" T5225860



WO 00/32353

PCT/GB99/04014

16

removal of material from the workpiece with the soft tool used at an angle in this embodiment,

Figure 16 is a diagram of the pattern of removal of material from the workpiece using the prior art technique,

Figure 17 is a graph of the pressure distribution across the diameter of the soft tool as it is pressed against the workpiece,

Figure 18 is a diagram illustrating the precession of a head at a precession angle  $\theta$ ,

Figure 19 is a diagram illustrating the calculation of the angle of the precession,

Figure 20 is a diagram illustrating the information of Figure 19 projected onto a sphere,

Figure 21 is a diagram illustrating the intersection of the tool and the surface of the workpiece,

Figure 22 is a cross section of the influence function,

Figure 23 is a two-dimensional map of the influence function of a tool,

Figure 24 illustrates the influence function projected onto a curved lens,

Figure 25 is an enlargement of a part of Figure 24,

Figure 26 illustrates the grooves or ablation profiles formed in the workpiece,

09857291.082001

WO 00/32353

PCT/GB99/04014

17

Figure 27 is a profile of a part made lens which requiring work,

Figure 28 is a graph of the dwell times required for polishing the lens,

5        Figure 29 is a forecast of the resultant profile using the dwell times of Figure 28,

Figure 30 is a flow diagram illustrating the polishing process,

10       Figure 31a and 31b are diagrams illustrating dynamic influence functions mapped onto a workpiece surface,

Figure 32 is a diagram showing surface roughness,

Figure 33 is a diagram showing polishing to reduce surface roughness, and

15       Figure 34 illustrates an alternative working member.

Figure 1 is a diagram of a polishing machine using a soft tool in accordance with an embodiment of the present invention.

20       A polishing machine comprises a robust table 1 resistant to vibrations. On the table 1 there is mounted an X-slide mechanism for movement in the x direction. On the X-slide mechanism 2 there is mounted a Y-slide mechanism 3 for movement in the y direction. On the Y-slide mechanism 3 there is mounted a turntable 4 for  
25       rotation in the direction of c. The turntable 4 is

T08280" T5225860

WO 00/32353

PCT/GB99/04014

18

mounted on the Y-slide mechanism 3 via a z movement mechanism (not shown) for movement of the turntable 4 in the z direction. The turntable 4 has a holding surface onto which a workpiece 5 is mounted for polishing or  
5 abrading. Thus this arrangement provides for motion of the workpiece 5 in four axis: namely x, y, z and c.

The polishing machine is also provided with a back member 6 on which is mounted a pivot arrangement for pivotally moving a polishing head 7. The polishing head  
10 7 is arranged for axial rotation and includes a working member 8 arranged at a lower axial end for polishing or abrading the workpiece 5. Thus the axial rotation of the working member 8 provides another axis for control: namely h.

15 The pivot mechanism mounted on the back member 6 comprises a first pivot member mounted 700 in an arm for pivoting the head 7 about a pivot point in the working member 8 in a first plane. The first pivot mechanism 700 is mounted on a second pivot mechanism 800 which provides  
20 for the pivoting of the head 7 about a pivot point in a plane perpendicular to the plane of pivoting of the first pivot mechanism 700 in the arm. Thus these two orthogonal pivoting mechanisms provide two further axes of control: namely a and b.

25 The back member 6 of the polishing machine also

T.0320 "T.62/5550

WO 00/32353

PCT/GB99/04014

19

houses a computer control system 9 which includes a display 10 and control inputs 11. This allows a user to input controls to control the motion of the workpiece 5 and of the working member 8 and to view displayed information regarding the polishing or abrading process.

Each of the axes of motion x, y, z, c, h, a and b are driven by respective drive mechanisms which in addition to driving motion in the axis, provides position information for use by the computer control system 9 to control the polishing or abrading process. The computer control system 9 is also provided with two further axes of control: namely the work done by the driving mechanism in rotating the working member 8 held on the head 7, and the pressure applied within the working member 8, as will be described in more detail hereinafter. Thus the computer control system 9 operates an algorithm which will be described in more detail hereinafter to control these nine axes in order to abrade or polish the workpiece 5 mounted on the turntable 4 to achieve a desired surface profile and/or surface quality such a smoothness. The apparatus can be used to achieve any desired surface profile including the surface profile containing both concave and convex areas.

The construction of the x and y slide mechanisms for driving the workpiece in the x and y directions, is

WO 00/32353

PCT/GB99/04014

20

conventional: merely comprising conventional linear slides. Thus the construction of these mechanisms need not be described in more detail.

The construction of the z and c axes drive mechanisms will now be described in more detail with reference to Figure 2.

Figure 2 is a partial view of the relevant mechanisms carried on the x slide mechanism 2. On the y slide mechanism 3 there is provided a mounting plate 12 extending underneath the y slide mechanism 3. The mounting plate 12 comprises an open box section in which is mounted the arrangement for moving the turntable 4 in both the z and c axes.

On a back face of the mounting plate 12 there is provided a guide mechanism 13 on which is mounted a motor housing 14 containing a motor 15 coupled via a shaft 16 to the turntable 4. The motor 15 is provided to rotate the turntable 4 in the c axis.

The motor housing 14 is arranged to be movable on the guide mechanism 13 in the z direction through the y slide mechanism 3. Since the turntable 4 moves in the z direction relative to an upper surface of the Y slide mechanism 3, rubber bellows 17 is provided to prevent the ingress of dirt into the mechanism.

00357291, 082801

WO 00/32353

PCT/GB99/04014

## 21

The motor housing 14 is driven in the z direction along the guide mechanism 13 by a motor 18 which drives a shaft 19 supported by a support 20. An upper end of the shaft 19 is formed to have a screw threaded portion 21 which co-operates with a threaded sleeve 22 fixably mounted on the motor housing 14. Thus rotation of the threaded portion 21 by the motor 18 causes motion of the motor housing 14 in the z direction which will cause the turntable 4 to move the z direction.

The mechanism for pivoting the head 7 will now be described in more detail with reference to Figure 3.

The head 7 is mounted at an upper end on a pair of parallel arcuate members 23. The arcuate members 23 have a radius of curvature centred on an axis BX which extends through the centre of the portion of the head 7 mounting the working member 8. The axis BX extends through the head 7 at a centre of the radius of curvature of the working member 8.

The head 7 includes a motor 24 driving a cog 25 to engagement with teeth on the arcuate members 23. The head is also provided with guide wheels 26 acting on either side of the arcuate members 23 in order to maintain the angle of the axis of the head 7 to the arcuate members 23. This arrangement ensures that as the

00857291.082801

WO 00/32353

PCT/GB99/04014

22

motor 24 drives the end of the head 7 in the direction b, the head 7 pivots about the axis BX.

The end of the head 7 near the motor 24 is provided with hydraulic pipes 27 for transmitting hydraulic pressure into the head 7 and to the working member 8 as will be described in more detail hereinafter. Also, in the head 7 there is provided a motor for rotating the working member 8 in the direction h. This will be described in more detail hereinafter.

The arcuate members 23 are mounted in the arm 7 on a mounting plate 28. The mounting plate 28 is mounted at an end to allow pivoting in a perpendicular plane.

The mounting plate 28 is mounted at a lower part of its ends on a pivot plate 29. The pivot plate 29 is pivotably mounted on a pivot point 30. The pivot point 30 is mounted on a lower part of a mounting plate 31.

An upper part of the end of the mounting plate 28 is mounted on a motor plate 32. On the motor plate 32 there is mounted a motor 33 for driving a cog 34. The mounting plate 31 is provided with an arcuate member 35 having a centre of its radius of curvature at the pivot point 30. The arcuate member 35 is provided with teeth to engage the cog 34 to allow the pivotal driving motion of the arm 7 about a pivoting axis AX which intersects the pivot axis BX at the portion of the head 7 near the working

WO 00/32353

PCT/GB99/04014

23

member 8. The point of intersection of the pivot axes AX and BX is the central of the radius of curvature of the working member 8. The motor plate 32 also mounts guide wheels 36 to guide the pivotal motion of the arm 7.

5 It can be seen from Figure 3 that the provision of the two orthogonal arcuate members 23 and 35 provide for the pivotal motion of the head about a virtual pivot point. This arrangement provides for the precession of the head about the virtual pivot point. It should be  
10 noted that the precession of the head can be undertaken as steps and need not be undertaken by taking an angular precession i.e. by rotating the upper part of the head through a circle. Instead, the upper part of the head mounted on the arcuate members 23 can move linearly to  
15 opposed precession positions. Patterns of movement of the upper part of the head will depend upon the pattern of precession required. Since the precession of the heads require considerable movement of the upper part of the head using the arcuate members 33 and 35, the  
20 preferred method of operation of the machine is to perform figuring of the whole of the workpiece (or as much of the workpiece as is necessary) using one precession position. The precession position can then be changed and figuring of the workpiece is carried out

09057291.082801



WO 00/32353

PCT/GB99/04014

24

again. This can be repeated for all required incremental precession positions.

Details of the construction of the head 7 and the working member 8 will now be described in more detail with reference to Figures 4 to 6.

The head 7 comprises a fixed part 37 and a rotating part 38. The rotating part 38 carries the working member 8.

An upper part of the head 7 comprises a block 39 to which the motor 24 is fixed. Extending from within the block 39 there is provided a stationary shaft 40. The stationary shaft 40 has a head 41 which is mounted at three points in the plane of this sectional diagram and at four equally spaced points in a plane orthogonal to this sectional diagram. The mounting points of the head 41 allow for the load experienced by the head 41 to be measured. In order to provide this there are provided three load cells 42 (two shown in the plane of this sectional diagram and one lying in the orthogonal direction). The load cells 42 are preloaded thus avoiding the need for five load cells; one for each mounting point of the head 41. The head 41 is mounted at each point, via load cell 42 where present, on support pins 43. The support pins include two waisted portions to reduce any lateral tension experienced by the load

09857291 082301

WO 00/32353

PCT/GB99/04014

25

cell 42. One end of the support pin 43 engages the head 41 at the mounting points. The other end of the support pin 43 is mounted on a steel ball 44 which sits in a cup 45 which is biased by a spring 46 against the block 39.

5 In this way, the head 41 of the stationary shaft 40 is allowed to move when both a lateral and vertical force is experienced by the shaft 40. The lateral and vertical loads on the shaft can be measured by the load cells 42. Lateral loads on the shaft 42 will be experienced due to  
10 a frictional force as the working member 8 engages the surface of the workpiece 5. The vertical force will be dependant upon the position of the head 7 in relation to the workpiece and the pressure within the working member 8.

15 To provide some rigidity to the support of the stationary shaft 40, the stationary shaft 40 is coupled to the block 39 by a resilient bellows 47. The stationary shaft 40 extends the length of the head 7 from the block 39 to a fluid chamber 48 sealed by the working  
20 member 8 at the lower end of the head 7. The stationary shaft 40 is hollow and contains fluid for the transmission of hydraulic pressure to the fluid chamber 48. Within the head 41 of the stationary shaft 40 there is provided two opposed inlets (only one shown) which  
25 connects to the hydraulic pipes 27 to allow for the

095791 03301  
T03230 T52/5360

WO 00/32353

PCT/GB99/04014

26

transmission of hydraulic pressure from outside the head  
7 to the fluid chamber 48.

Below the block 39, the stationary part of the head 7 includes a motor housing 50 enclosing a stator 51 and a rotor 52. The stator 51 is fixed to the motor housing 50. The rotor 52 is fixed to a rotating sleeve 53 which rotates about the stationary shaft 40 and within the motor housing 50. The rotating sleeve 53 is mounted on upper bearings 54 and lower bearings 55 within the motor housing 50. At an upper end of the rotating sleeve 53 there is provided a position encoder 56 for providing a signal indicating the speed of rotation.

The lower end of the rotating sleeve 53 extends out of the motor housing 50 around the stationary shaft 40 to drive the rotating part 38.

Figure 5 shows in more detail the interface between the stationary part 37 and the rotating part 38.

As can be seen more clearly in Figure 5, the lower bearings 55 are held in position by a bearing ring 57 which has an inner screw thread to engage an outer screw thread on a lower part of the rotating sleeve 53. The lower part of the rotating sleeve 53 carries a spoked member 58. The spoked member 58, as shown in more detail in Figure 6, has an inner annular ring 58b for engaging the lower part of the rotating sleeve 53 and this is held

WO 00/32353

PCT/GB99/04014

27

in place by a locking ring 59. The spoked member 58 includes spokes 58a extending from the inner annular ring 58b to an outer annular ring 58c. The outer annular ring 58c engages the rotating part 38 in order to drive the rotation thereof. The purpose of the spoked member 58 is to provide rotational coupling between the rotating sleeve 53 and the rotating part 38 whilst allowing translational and vertical forces experienced by the rotating part 38 to be transmitted along the stationary shaft 40 to be detected by the load cells 42.

The rotating part 38 comprises a housing 60 rotationally carried by bearings 61 on the stationary shaft 40. The bearings 61 are held between an upper locking ring 62 and a lower locking ring 63. An upper plate 64 is provided to act with the housing 60 to clamp the outer annular ring 58c of the spoked member 58. The upper plate 64 is also provided with a dirt ingress prevention arrangement comprising two concentric sleeves 65 each with holes 66 provided at lower regions thereof. The sleeves 65 extend into an annular recess provided in a lower part of the motor housing 50. This arrangement provides a long path length for the ingress of dirt into the bearing 55 and 61. Any dirt which should find its way in past the sleeves 65 will tend to be thrown out to the holes 66 by centrifugal action.

WO 00/32353

PCT/GB99/04014

28

Within the housing 60 there is provided a fluid seal 67 to provide a seal between the housing 60 and the stationary shaft 40.

Fixed to the housing 60 is a tool housing 68 on to which is mounted a membrane 69. The membrane 69 is bulbous and is held at its periphery in the tool housing 68. The periphery of the membrane 69 comprises a cylindrical portion which fits into a cylindrical recess of the tool housing 68. A clamping ring 70 is provided to clamp the membrane 69 against the inner face of the tool housing 68. The tool housing 68 and the membrane 69 together form the fluid chamber 48 which communicates with the passage within the stationary shaft 40 to allow for hydraulic pressure to be transmitted via the hydraulic pipes 27 to the fluid chamber 48. The control of the pressure within the fluid chamber 48 controls the stiffness of the resilient working member 8. The hydraulic pressure in the fluid chamber 48 is a parameter which is controlled during the polishing or abrading operation of the machine.

The housing 60 is provided with fluid bleed passages 71 to allow for the bleeding of any air within the fluid chamber. The fluid chamber is filled with an incompressible fluid such as an oil-in-water emulsion or glycol.

T032353 16225860

WO 00/32353

PCT/GB99/04014

29

A removal abrasive cup 101 is provided over the membrane 69 to provide the working member 8 with a working surface for polishing or abrading the workpiece. This will be described in more detail hereinafter with reference to Figure 9.

Thus it can be seen from Figures 4 to 6 that this arrangement provides not only for the control of the pressure within the fluid chamber 48, but also allows for the measurement of the translational and vertical forces experienced by the working member 8 when rotating against the workpiece surface.

The embodiment of the invention illustrated in Figures 4 to 6 does not allow for the easy replacement of the working member 8 since the fluid seal will be broken.

Figures 7 and 8 illustrate an alternative embodiment wherein the housing 60, the tool housing 68 and the membrane 69 are replaced with an alternative arrangement. In this embodiment of the present invention a housing 80 allows for the interchanging of tool housings. In Figure 7 the tool housing 81 holds a small sized membrane 82. In Figure 8, the tool housing 83 has a large sized membrane 84.

The housing 80 is provided with a threaded axial recess 85 to receive a threaded portion 86a or 86b of the tool housing 81 or 83. Within the recess 85 the housing

WO 00/32353

PCT/GB99/04014

30

80 is provided with a pressure transmission membrane 87 extending across a small fluid chamber 88 and held in place by a clamping ring 89. The housing 80 is also provided with a bleed port 90 for the bleeding of air out of the chamber 88.

Thus, fluid pressure transmitted down the cavity of the stationary shaft 40 is transmitted to the fluid chamber 88 which transmits the pressure to the pressure transmission membrane 88.

The tool housing 81 or 83 is provided with a similar opposed pressure transmission arrangement comprising a pressure transmission membrane 91 held in place by a clamping ring 92. The pressure transmission membranes are arranged to contact one another to allow for the transmission of fluid pressure across the membranes whilst allowing the housing 80 and the tool housings 81 or 83 to be separated without breaking the hydraulic seal.

Within the tool housing 81 and 83, the respective membranes 82 and 84 form respective fluid chambers 93 and 94. As for the previous embodiment illustrated in Figure 4, the membranes 82 and 84 have an outer periphery forming a sleeve which fits in a recess in the respective tool housings 81 and 83. Respective membranes 82 and 84 are held in place by respective clamping rings 95 and 96.

WO 00/32353

PCT/GB99/04014

31

An outer region of the tool housing 81 and 83 adjacent to the respective membranes 82 or 84 is formed into a cylindrical face 97 and 98 with a slight taper (2°) away from the membrane 82 and 84. The formed tapered face 97 and 98 is for receiving an abrasive cup as will be described in more detail hereinafter.

As can be seen in the drawings, the membranes 82 and 84 comprise thin membranes that can deform when they contact the surface of the workpiece. They are able to conform to the surface of the workpiece. The area of contact between membrane 82 or 84 and the surface of the workpiece will depend upon proximity of the tool housing 81 or 83 to the surface of the workpiece: the closer the tool housing 81 or 83 comes to the surface of the workpiece, the more compressed the membrane 82 or 84 will become and thus there will be a larger area of contact between the membrane 82 or 84 and the surface of the workpiece.

Because the membrane 82 or 84 is clamped internally so that its outer surface clamps to the inner surface of the tool housing 81 or 83, its outer dimensions will not vary in accordance with the degree of force using in clamping. This ensures uniformity of the size of the working member in view of the replaceability of the membrane 82 or 84.



WO 00/32353

PCT/GB99/04014

32

When building the interchangeable tool heads, the fluid chambers 93 and 94 can be filled with fluid by assembling the tool heads immersed in the fluid i.e. the pressure transmitting membrane 91 can be clamped when the tool is submerged in the fluid.

The radius of curvature of the membranes 82 and 84 is larger than the radius of the aperture into which it fits in the tool housing 81 or 83. In this way the membrane only comprises an arcuate portion and not a hemispherical portion. Thus the total curvature of the bulge of the membrane 82, 84 is not large. This is important when consideration is given to the application of an abrasive sheet material to the membrane 82 or 84.

The fitment of an abrasive cup to the tool head will now be described with reference to Figure 9.

The tool head comprises the membrane 100 and a tapered cylindrical surface 99 which tapers away from the membrane 100 to receive the abrasive cup 101. The abrasive cup 101 comprises a cylindrical sleeve 102 having slots 103 cut into an upper end thereof. At a lower end of the sleeve 102 a working material 104 is arranged over the sleeve 102 and clamped around the sleeve 102 by clamp 105. The working material 104 can also be fixed by adhesive to ensure that it could not become separated from the sleeve.

WO 00/32353

PCT/GB99/04014

33

The abrasive cup is arranged to fit over the tapered cylindrical surface 99 of the tool head. By clamping the upper part of the sleeve 102 using a clamp 106, the sleeve 102 can be made to contract and grip onto the tapered cylindrical surface 99. In this way the working material 104 is laid over the membrane 100. Because the cylindrical surface 99 is tapered, it cannot work loose during abrading or polishing. This is important, since if the ring were to come loose during polishing or abrading, serious damage to the workpiece could be inflicted.

The working material can be a conventional polishing cloth material with which an abrasive slurry is used. Alternatively, the working material can comprise a sheet with an abrasive material bonded thereto or impregnated therein so that when polishing, an additional abrasive material e.g. a polishing paste is not necessary. It is only necessary in this latter embodiment to use a fluid to cool the workpiece and tool, to lubricate the polishing process, and to carry the abraded particles away from the polishing area. With a careful selection of bonded abrasive material, this can increase the predictability of the polishing process.

The choice of abrasive material bonded on the tool impregnated in the sheet will depend upon the

WO 00/32353

PCT/GB99/04014

34

application. For example, when polishing glass diamond is not usually suitable for achieve the finest optical finish and materials such as cerium oxide or aluminium oxide are normally used for finishing. For grinding or abrading, it is possible to use nickel bonded diamond pellets on a fabric or plastics base whereas for polishing materials other than glass and for the initial polishing of glass it is possible to use an epoxy bonded diamond sheet in the form of epoxy-diamond pellets. The bonded abrasive material can be applied to the sheet as beads thus providing localised polishing areas with spaces therebetween. This helps the removal of the abraded material by allowing it to pass between the beads of bonded abrasive material and provide the required flexibility.

Where a softer abrasive material is required, this can be mounted in a binding material which is designed to breakdown at a sufficient rate to expose fresh abrasive material so as to be available for the polishing action. It is thus known that an erosion promoting material can be added to the matrix material to be used to bind an abrasive material together in order to ensure that the matrix binding material will erode at a sufficient rate to expose abrasive material. (See for example a paper by B.E. Gillman et al entitled "Bound-Abrasive Polishers for

WO 00/32353

PCT/GB99/04014

35

Optical Glass" in Applied Optics Vol. 137 No. 16, 1988 pages 3498 to 3505).

5 In order to provide a better polishing process solid lubricant particles are provided in the matrix as well as the abrasive material. This reduces friction between the matrix material and the glass and stabilises the lubrication of the abrasive action. Such lubricant particles can for example comprise talc particles (magnesium silicate). If such a lubricant is used, the matrix can comprise rubber since the friction between the workpiece e.g. glass and the matrix is reduced.

10 The sheet 104 must be sufficiently flexible to flex when the membrane 100 is displaced during polishing. Since the sheet 104 is separate from the membrane 100, it must have good torsional strength in order to survive the polishing process without deforming e.g. creasing. During a typical polishing process, a 3 kilogram drag can be experienced by the polishing sheet 100.

15 Since the sheet 104 has a larger radius of curvature than the membrane 100, during polishing, when the membrane 100 is deformed by pressure on the workpiece, there will need to be some lateral movement between the sheet 104 and the membrane 100. Thus the inner surface of the sheet 104 and/or the surface of the membrane 100 should provide such. This can be provided by applying a

20

25

WO 00/32353

PCT/GB99/04014

36

material between the membrane 100 and the sheet 104 when the abrasive cup 101 is fitted to the tool head unit. For example, a lubricant can be placed between the sheet 104 and the membrane 100. The use of such a lubricant, however means that the sheet 104 can gain no torsional support from the membrane 100 and will simply slide over it. Instead, a non-curing or unset adhesive can be used which allows lateral movement but provides some adhesive properties between the membrane 100 and the sheet 104. Because of the nature of the unset adhesive, it is also possible to easily remove the abrasive cup from the tool head unit. This avoids the need to retrieve the tool head which would be necessary if the abrasive was bonded directly to the membrane 100 or a slurry was used. Also, the abrasive will wear out and need replacing regularly. Further, different grades of abrasive will be needed for different polishing stages and thus different abrasive cups can easily be interchanged.

The sheet 104 can be formed from a substrate sheet material cut in a form as illustrated in Figure 10. Holes are cut in the sheet to enable it to be deformed into the curved shape necessary to lie over the membrane 100. The sheet material used can either be a polishing cloth material to which an abrasive slurry must be added, or the sheet can be a sheet having abrasive material

WO 00/32353

PCT/GB99/04014

37

bonded thereto. It is also possible to use sheet illustrated in Figure 10 merely as a substrate onto which can be mounted a working material. Figure 11 illustrates a shape of such a piece which can be cut and formed on to the sheet 104. Once again the material can either comprise a conventional polishing cloth with which a conventional abrasive slurry must be used, or can be formed of a sheet material having abrasive bonded to or impregnated in the sheet.

10 A method of forming an abrasive cup will now be described with reference to Figures 12 and 13. In the first step S1 the sleeve 109 is arranged around a cylindrical former 111 having a convex end. A sheet of polishing material 110 is arranged over the convex end of the former 111. In step S2 the edges of the sheet of polishing material 110 are adhered to the outer surface of the sleeve 109 and are clamped in place using a clamp 112. Then in step S3 the sheet of polishing material 110 is pressed between the convex face of the former 111 and a concave face of a former 113. In this way the convex shape required for the sheet of polishing material 110 is achieved. Then in step S4 the two formers 111 and 113 are retracted allowing the removal of the abrasive cup.

The abrasive cup can be used for grinding or polishing. Also, the abrasive cup can be used in an

WO 00/32353

PCT/GB99/04014

38

intermediate process ductile mode grinding. In this mode the workpiece surface is removed by the cutting action of the bound abrasive particles in the form of fine swarf. This is distinct from the chips produced in fracture mode grinding. Ductile mode grinding gives a better finish with much less sub-surface damage. The mode is achieved by the choice of pressure and speed for a given abrasive.

The operation of the polishing apparatus will now be described hereinafter wherein the head assembly is controlled so as to present the head unit (8) at an angle away from normal to the surface of the workpiece.

Figure 14a illustrates the application of the working member unit 8 against the workpiece 5. The cup membrane 110 complies to the surface of the workpiece 5. The dotted line in Figure 14b illustrates the removal profile obtained using the working member 8 based perpendicularly to the workpiece 5 and rotated about its axis. Figure 15 illustrates the abrasive action of the working member 8 against the workpiece 5. As can be seen because there is zero rotation at the centre of the area of contact the removal rate at the centre is zero. This removal profile is disadvantageous since it is difficult to achieve the desired profiling across the workpiece using such a removal profile. The inventors have thus realised that by tilting the working member 8 at an angle

WO 00/32353

PCT/GB99/04014

39

8 to the normal to the workpiece 5 and moving it to  
precessed positions, is possible to obtain the removal  
profile illustrated in the dotted line in Figure 16.  
Because there is no stationary region anywhere i.e. the  
5 centre of rotation of the membrane 110 is not on the  
surface of the workpiece, there is no area of zero  
removal. This removal profile is thus nearer a desirable  
Gaussian profile.

Figure 17 illustrates the pressure distribution  
10 across the workpiece provided by the soft tool of this  
embodiment. As can be seen there are no sharp  
discontinuities in the pressure. It is provided evenly  
across most of the area of contact and decays slowly at  
the edges because of the soft nature of the tool.

15 It can be seen in Figure 14b that tilting the axis  
of rotation of the tool away from normal to the workpiece  
and precessing it provides a better removal profile. The  
method of removal comprises an abrasive action as shown  
in Figure 19 for no precession, this can lead to  
20 scratches or grooves being formed in the workpiece in  
much the same way as the action of an abrasive belt. In  
order to avoid any possibility of such scratches or  
grooves remaining, the polishing action carried out by  
the polishing machine is not merely the polishing by  
25 tilting of the working member 8 at an angle to the normal



WO 00/32353

PCT/GB99/04014

40

to the surface, but includes the polishing of the workpiece at the angle precessed about the normal. This is illustrated in Figure 18. N indicates the direction normal for the workpiece W, and P indicates the polishing direction i.e. the direction of rotation of the working member. The working member 8 thus rotates about the polishing direction at an angle  $\theta$  to the normal N but the polishing direction P also rotates or precesses around the normal N. The result of this is that at each position around the precession a polishing action illustrated in Figure 15 is carried out at a rotated angle dependent upon the angle of precession. Thus each time the vector P is moved around the normal N by an angle the polishing effect illustrated in Figure 15 is rotated by that angle. Thus once a complete precession has taken place, the pattern in Figure 15 has been applied at all angles of rotation. This has the affect of averaging out the pattern of polishing thus reducing the likelihood of any defects being caused by the polishing pattern.

Because the workpiece being polished is generally not flat, the diagram of Figure 18 is an oversimplification.

Figure 19 illustrates the practical position wherein the normal to the workpiece surface continually changes

09857291 092801  
T08280 T622960

WO 00/32353

PCT/GB99/04014

41

dependent upon the position of the workpiece to be polished. Of course, the vertical V to the workpiece defined as the z axis remains constant. Thus the angle of polishing  $\theta_2$  is the summation of the precession angle  $\rho$  plus the angle  $\theta_1$  at which the normal N is to the vertical V. Although in Figure 19, all the angles are shown in a single plane, of course, these angles are angles in three dimensions.

Figure 20 is an illustration of the same information projected onto a sphere. V, N and P have the same meanings as in Figure 19. This diagram defines these three directions in space. When precessing, angle  $\gamma$  changes and angle  $\rho$  stays constant. Angles  $\alpha$  and  $\beta$  are the two driven angles in the pivot mechanism which have to be computed from displacements a and b in order to control the pivot mechanism.

The slope of the workpiece's surface at any point will be calculated as described in more detail hereinafter given  $\phi_1$  and  $\theta_1$ . The polishing routine for the particular task will have  $\rho$  and  $\gamma$  as given data (which may change during the run). To find the driven angles  $\alpha$  and  $\beta$ , it is first necessary to find  $\theta_2$  and  $\phi_2$  from:

$$\cos \theta_2 = \cos \rho \cdot \cos \theta_1 + \sin \rho \cdot \sin \theta_1 \cdot \cos \gamma \quad (1)$$

$$\sin(\phi_1 - \phi_2) = \sin \rho \cdot \sin \gamma / \sin \theta_2 \quad (2)$$

WO 00/32353

PCT/GB99/04014

42

$$\cos(\phi_1 - \phi_2) = (\cos(\rho) - \cos(\theta_2) \cdot \cos(\theta_1)) / (\sin(\theta_2) \cdot \sin(\theta_1)) \quad (3)$$

The use of equations 2 and 3 enables the solution for  $(\phi_1 - \phi_2)$  to be placed in the correct angular quadrant.

Having  $\theta_2$  and  $\phi_2$  we can find the gimbal drive angle  $\alpha$  and  $\beta$  from:

$$\alpha = \tan^{-1}(\cos \phi_2 \cdot \tan \theta_2) \quad (4)$$

$$\beta = \sin^{-1}(\sin \phi_2 \cdot \sin \theta_2) \quad (5)$$

The apparent signs of the angles  $\alpha$  and  $\beta$  will depend on the drive systems of the pivot and will need to be set by inspection.

The usual precautions in computing are necessary to deal with division by zero if occurring in equation 2.

The determination of the slope surface of the workpiece will depend upon the position on the workpiece and the surface shape.

One particular shape that is important in optics is the "even asphere". The "even asphere" is used for a surface which is part of a sphere at the very centre, but with edges which are raised or lowered more than the spherical curve. Such a shape can either be concave or convex.

If in the x, y and z axis, z is the height which increases positively as we move upwards from the plane of

 0057291.08301  
 108280"152580

WO 00/32353

PCT/GB99/04014

43

the turntable, positive  $z$  on a glass workpiece will always correspond to more glass. In accordance  $x$  and  $y$  are positioned to be horizontal to the plane of the turntable and centred on the axis of the turntable. Thus  $x$ ,  $y$  and  $z$  are right handed axis. The formula for the even asphere is a height  $z$  as function of  $x$  and  $y$ :

$$z = c.r^2/(1+A) + a_2.r^2 + a_4.r^4 + a_6.r^6 + a_8.r^8 \dots$$

where  $r^2 = x^2 + y^2$ , (6)

$$A = \sqrt{1 - (k + 1) c^2 r^2},$$

and  $c$ ,  $k$ ,  $a^2$ ,  $a^4$  etc are the constants which define the surface required on a particular workpiece.  $c$  is the reciprocal of the radius of curvature of the central sphere.  $k$  is referred to as the conic constant, which is defined by this formula. If all of the constants are zero, the surface is flat, and if just  $c$  is non zero the surface is a sphere. Various values of  $k$  are used for defining paraboloids, ellipsoids and hyperboloids of revolution.

In order to determine the slope or gradient of the curved surface at the contact point of the tool, equation (6) is differentiated. This gives the gradient of the required surface in the radial direction as:

$$dz/dr = c.r/A + 2a_2.r + 4a_4.r^3 + 6a_6.r^5 + 8a_8.r^7 \dots (7)$$

The angles defining the normal line  $N$  are thus given

as:

WO 00/32353

PCT/GB99/04014

44

$$\theta_1 = \text{angle VP} = - \tan^{-1} dz/dr \quad (8)$$

The sloping angle at the contact point is given by:

$$\phi_1 = \tan^{-1} y/x \quad (9)$$

5 where  $x, y$  is the contact point. These angles of the surface normal are for any axially symmetrical lens. For asymmetrical lenses its surface equation must be substituted to find  $\theta_1$  and  $\phi_1$ .

10 The angles  $\theta_1$  and  $\phi_1$  are computed and used in equations 1 and 2 to give the pivot drive angles for a lens.

15 So far no consideration has been given to the fact that the pivot point of the pivot arrangement is not at the centre of point of contact on the surface of the workpiece. It is at or near the centre of curvature of the membrane and thus when the pivot arrangement is rotated at any angle  $\theta_1$  and  $\phi_1$  if no compensation is made for the displacement of the pivot point away from the surface of the workpiece, the head unit would move substantially in any of the  $x, y$  and  $z$  directions. Thus  
20 this embodiment of the present invention avoids this problem by compensating for the shift in  $x, y$  and  $z$  co-ordinates generated by rotation in angles  $\theta_1$  and  $\phi_1$ . The compensation can either take place in the form of real time calculations using the equations given hereinafter,

T08280" T62/5860

WO 00/32353

PCT/CB99/04014

45

or the calculations could be carried out for the angle  $\theta_1$  and  $\phi_1$  beforehand and stored in a look-up table.

The other point to be taken into account when calculating the position of the centre of the point of contact is the compressibility of the soft tool.

The centre point of the pivot is a distance D from the centre of the tool polishing face when the tool is not compressed. The tool is compressed by a distance d measured in a direction which is normal to the surface of the workpiece.

The coordinates x, y and z find the centre of the tool contact position after compression and tilt with the tool i.e. the centre of the area which has been worked.

$\theta_1$ ,  $\phi_1$ ,  $\theta_2$ , and  $\phi_2$  are the angles of the surface normal and tool spin.

X, Y and Z define the centre of the pivot mechanism.

D is the distance from the centre of the pivot to the uncompressed tool tip.

d is the amount by which the tool surface is compressed e.g. 0.3 mm.

T is the radius of curvature of the spherical tool tip e.g. 30 mm as shown in Figure 20.

The equations defining the centre of the pivot mechanism are:

$$X = x + (T-d) \cdot \sin\theta_1 \cdot \cos\phi_1 + (D-T) \cdot \sin\theta_2 \cdot \cos\phi_2 \quad (10)$$

WO 00/32353

PCT/GB99/04014

46

$$Y = y + (T-d) \cdot \sin\theta_1 \cdot \sin\phi_1 + (D-T) \cdot \sin\theta_2 \cdot \sin\phi_2 \quad (11)$$

$$Z = z + (T-d) \cdot \cos\theta_1 + (D-T) \cdot \cos\theta_2 \quad (12)$$

Thus, using the equations given hereinabove, the movement of the working member 8 caused by the precession can be corrected.

As mentioned above, because of the precession, the non-axially symmetric ablation carried out by the tool at an angle is averaged to a substantially axially symmetric ablation pattern by precession.

The precession operation can be carried out at each polishing location so that the working member 8 is arranged to precess through at least 360 degrees about the normal to the workpiece. However, a more efficient method is to cover a required area of the tool using one precession angle, increment the precession angle, and then polish the area again. This has the same averaging effect but reduces the amount of pivot arrangement movement required and speeds up the polishing process. The required areas can be concentric annuli resulting from the applications of the tool and the rotation of the turntable carrying the workpiece.

In this embodiment the increment of the precession angle around the normal is chosen to be an integer fraction of 360 degrees in order to provide a symmetric distribution of precession angles.

WO 00/32353

PCT/GB99/04014

47

One advantage of using the precession of the soft tool instead of rotating it with an axis normal to the surface of the workpiece as performed in the prior art is that the tool is self wetting. Because of the non-axially symmetric ablation pattern, the fluid e.g. water used for wetting the abrasive material or the abrasive slurry is drawn under the tool by the lateral movement. In contrast, using a conventional rotating tool, the polishing material thereunder tends to be thrown out regularly.

The control of the polishing apparatus by the computer control system 9 will now be described in more detail.

The computer control system 9 controls the x, y and z axis movement, the a and b axes, the spin h of the head 7, the speed of the turntable C, the motor power for rotating the working member 8, and the hydraulic pressure within the tool. It is also possible to control the feed of slurry or the lubricating/cooling fluid. These variables may be controlled to maintain at a desired level the rate of mechanical work (watts) done by the abrasion of the tool against the workpiece. The rate of work is computed from the motor speed and current (which may be monitored by standard methods), and using data



WO 00/32353

PCT/GB99/04014

48

provided by the manufacture of the motor, this control of the rate of work enables accurate control of the rate of material removal.

In this embodiment the computer receives no feedback on the x, y and z, a and b coordinates. These are based on dead reckoning. The tool spin speed is measured and the work done by the motor is monitored. The turntable speed can also be controlled. The vertical and lateral load on the tool is measured by the load cells 42.

The program within the computer control system 9 operates an algorithm in order to receive as an input the desired surface form. Also the current surface form of the workpiece 5 is obtained by measurement and thus a form error is determined i.e. determination of the amount of material to be removed across the surface is determined. Also the influence function i.e. the removal rate pattern (as it is modified by the action of precession) of the soft tool is determined and used to determine a pattern of polishing.

The type of abrasive to be used is selected dependent upon the amount of material to be removed, and the type of material. This will determine the pressure to be applied to the workpiece. Using the information on the form error and the pressure required, a contact area for the soft tool over the surface can then be

WO 00/32353

PCT/GB99/04014

49

determined. This of course can vary dependent upon the form error pattern. Using the influence function a pattern of removal can then be estimated in order to move from the current workpiece form to the target form. Typically the algorithm will only attempt to reach 80% of the target in order to avoid over shooting i.e. removing too much material. The process can however, iteratively repeat in order to achieve the target form.

The parameters which can be controlled are the dwell time, the contact area, the head rotation speed, the workpiece rotation speed, the pressure on the workpiece, the force on the workpiece and the fluid pressure.

Computation of the required dwell times, in order to achieve the target surface, is carried out using a numerical optimisation process. The dwell times are calculated for the position of the tool in relation to relatively proud features on the surface of the workpiece. The longer the dwell time, the more the proud feature is reduced. The aim of the numerical optimisation is to minimise the "sum of squares" height remaining after the process.

A given tool operates with given compression and speed, and through a given precession cycle, provides a local "influence function" i.e. a local area of workpiece removal which is characteristic of the tool and the

WO 00/32353

PCT/GB99/04014

50

variables in its use. This influence function is measured experimentally. A cross-section of such a function is shown in Figure 22 from centre to edge. It represents the depth of possible workpiece removal at a fixed position per second. This may also be represented as a map and is illustrated in Figure 23. For an off-centre part of the optical surface which will in general be sloped in relation to the plane of the x y axis, the influence function appears slightly fore-shortened in projection into that plane as shown in Figure 24. The contour area is enlarged in Figure 25.

Referring back to Figure 22, for a radial figuring pattern, as the workpiece is rotated on the turntable, the local influence function is drawn out into a groove. A series of grooves is possible for different radii on the workpiece and cross-sections of the grooves are shown in Figure 26, again in units of depths per second. It should be noted that there is less removal on outer parts of the workpiece as the effective removal is distributed all around the workpiece instead of being more concentrated in the centre i.e. the circumference of the circles traced by the head are longer. The actual workpiece (glass) removal is given by the shape of one of the profiles multiplied by the time in which the tool works in that profile (the dwell time). By choosing a

WO 00/32353

PCT/GB99/04014

51

5 dwell time in each groove, various overall shapes for  
glass removal measured along a radius of the lens may be  
obtained. For example, a profile of a part made lens  
surface requiring work is illustrated in Figure 27. It  
has a form error defect consisting of an annular raised  
area, whereas the centre and edge of the lens are at  
almost the required height. By using a standard least  
squares algorithm for optimisation, the dwell times  
required for each radius on the lens, to remove the  
10 annular raised areas are computed. This is shown in  
Figure 28. By multiplying each groove profile by the  
corresponding dwell time and adding this computed affect  
to the profile shown in Figure 27 a forecast for the  
resulting profile is obtained as shown in Figure 29. The  
15 area of the surface of the surface which is considered  
has been affectively flattened and this confirms the  
correctness of the computation.

In computation of the required dwell time, a  
feedback process can be used for correcting errors in the  
20 glass removal process, such as might be caused by  
slackness in gears, lack of straightness in the  
mechanical slides, or changes in general operating  
conditions such as humidity or temperature.

The feedback process requires the analysis of the  
25 actual glass removal after a grinding or polishing run.

WO 00/32353

PCT/GB99/04014

52

The result of the analysis is a set of dwell times giving a least square fit for glass removal. The dwell times are retrospective times which the machine would have been expected to use to achieve such a removal. The feedback information is obtained by comparing the notational retrospective values with those which are actually replied. The comparison takes the form of finding the ratio of real to retrospective dwell times. The result of the comparison is a correction. Examples of the corrections are: (1) a constant ratio factor by which the computed dwell times for real glass removal should be increased or decreased to give the required results and (2) a set of such ratios used as correction factors for the dwell times, the set corresponding to a set of different positions on the workpiece.

The determination of correction factors is also important for machine engineering and maintenance purposes since they will indicate defects in operation.

The numerical optimisation process can also determine the desired contact area between the tool and the workpiece. This is achieved simply by using more than one influence function. A further set of ablation profiles (typically cross-sections of grooves) is obtained for each additional influence function. The result of the numerical optimisation then includes dwell

WO 00/32353

PCT/GB99/04014

53

times for each set of ablation profiles. The nature of an optimal result is that if a given profile is not advantageous, then a zero or very small dwell time will be assigned to it. Thus the assignment of significant dwell times to certain ablation profiles selects a tool contact area.

The process of determining dwell times will now be described with reference to flow diagram of Figure 30. The shape of workpiece surface to be polished is determined by measurement (step S10). Data defining the desired shape is input in step S11 and in step S12 the desired shape data is subtracted from the determined data to obtain shape error data.

The influence function for unit dwell time is then mapped for the predetermined positions in step S13. In this embodiment a separate map is generated for each influence function i.e. a single curve of Figure 26. Initial dwell times are then input in step S14 to start the optimisation process. The initial dwell times chosen can be any arbitrary initial values such as a unit time for all positions. The mapped influence functions are then multiplied by the input initial dwell times and the maps are added to determine a predicted removal map (step S15). In step S16 the predicted removal map is subtracted from the form error to determine a list of

WO 00/32353

PCT/GB99/04014

54

height errors for the predetermined positions. It is these height errors which define the error between the desired shape and the predicted polish shape which is to be minimised by the least squares algorithm. Thus these values are input into the least square algorithm and in step S17 the algorithm attempts to minimise the errors. In step S18 it is determined whether the optimisation is finished. If not, in step S20 the algorithm creates a new case set of dwell times and the process returns to step S15 to repeat the minimisation process.

If in step S18 the optimisation process has finished, in step S19 the dwell times determined are translated into velocities for the polishing head for positions for figuring patterns. Then in step S21 the machine polishes the workpiece used in the determined velocities.

The process can be repeated by returning to step S10 to measure the shape to see if the desired shape is actually be achieved. If not, steps S11 to S21 can be repeated.

While this process has been described hereinabove, in respect of a 2D process, the process is equally applicable to a 3D process for use with a 3D influence function, a 3D desired shape, and a 2D array of

00957291.08201  
T03230.1627560

WO 00/32353

PCT/GB99/04014

55

predetermined positions for the computation of dwell times thereat.

In the 3d arrangement, there is a far greater control of the polishing since, unlike the 2D arrangement, the same radial positions can be polished  
5 differing. The numerical optimization problem merely becomes one of the determining dwell times for a 2D, rather than a 1D, array of points. If there are potentially a large number of points, thus making the  
10 process potentially lengthy, a small array of points can be chosen e.g. by dividing the area into segments and processing separately, or by providing positions over the area which are separated by large gaps. In the latter process, each figuring pattern is unlikely to pass over  
15 a sufficient number of closely arranged positions for the determination of dwell times (i.e. the speed of the polishing head along the path). In this case, dwell times or points along the figuring pattern can be determined by a process of interpolation between the  
20 predetermined positions.

In the 2D and 3D embodiments described hereinabove, the dwell times used are for static influence functions which define the removal profile at a position for a unit time. This does not however take into account that  
25 instead of the tool head being lifted and placed at each

00557291 082804  
T082804 1622860



WO 00/32353

PCT/GB99/04014

56

position, the preferred technique is to continuously move the tool head over the surface of the workpiece. Thus, there is no position at which the head dwells. The inventors have therefore developed a dynamic dwell time technique. In this technique an influence function is defined as the removal profile for a unit tool head velocity for a particular figuring pattern. This is determined by projecting the static influence function along the figuring pattern at a predetermined (e.g. unit) velocity.

Figures 31a and 31b illustrate two different types of dynamic influence functions mapped onto a surface to be polished. Figure 31a illustrates a rastering figuring pattern, Figure 31b illustrates a circular figuring pattern.

Figure 31a illustrates three dynamic influence functions applied to three positions  $P_1$ ,  $P_2$  and  $P_3$ . It should be noted that the dynamic influence function has the same shape for each position since the figuring pattern 200 is the same at each position i.e. linear.

In Figure 31b, the figuring pattern 201 is circular and thus as can be seen in the diagram the figuring pattern for different radial positions changes shape. At the centre position  $P_1$  the pattern is circular whilst a

WO 00/32353

PCT/GB99/04014

57

radial positions  $P_1$  and  $P_2$ , the dynamic influence function is extended along the figuring path.

This technique will result in the determination of velocity for the tool head at positions (e.g.  $P_1$ ,  $P_2$ , and  $P_3$ ) across the workpiece surface to be polished. Thus in this embodiment step S19 of Figure 30 is not required.

It will thus be apparent to a skilled person in the art that because this aspect of the present invention operates to optimise dwell times or tool speeds for positions on the workpiece, a simple process of optimising the values can be used. Any numerical analysis technique can be used to optimise values to achieve a desired result e.g. a desired mean error.

In the present invention at least one cost function can be minimised. The cost functions can include:

1. Height errors
2. Gradient errors
- 3 Total polishing time
4. Excess of tool speed over a limit

The cost functions can be appropriately weighted.

For numerical analysis the cost functions are appended series of numbers to be optimised by the algorithm.

25

WO 00/32353

PCT/GB99/04014

58

So far in the embodiments, only the removal of material in order to achieve the desired shape has been considered. However, polishing requires not only the required shape but also the required surface roughness (micro-roughness).

An optical or other polished surface can have quality failings in terms of micro-roughness, as well as the more obvious large-scale form errors. Micro-roughness is a property of the surface often conventionally expressed as the average local height departure from a well-smoothed surface and denoted as Roughness Average "Ra". The present invention can provide a roughness-reduction method by the appropriate operation of the precessed tool.

Micro-roughness is measured with equipment such as interferometers operated through microscopes (for example, the proprietary WYKO NT 2000 interferometer) or with contact methods (for example, the proprietary Taylor Hobson Talysurf). The roughness at various stages in the polishing process may be measured at different stages of production for the first workpiece in a production run of similar workpieces, and thenceforth may be considered well enough known during the process.

In the method of this embodiment there are alternative criteria for commencing roughness-reduction.

WO 00/32353

PCT/GB99/04014

59

It is commenced if measurement shows that the form of the workpiece is already within acceptable limits apart from its roughness quality. A typical case is that the form is correct within a customer's requirement of 100 nanometres peak-to-valley form error, but parts of the surface exhibit Ra values of 10 nanometres or more, whilst a finished quality of Ra less than 3 nanometres is required. It is also economic to commence roughness reduction if measurement shows that the less than a further 100 nanometres of workpiece material (usually glass) has to be removed to meet the specified form of the surface within tolerances. if this small amount of material were removed without the roughness-reduction technique, that technique could still need to be applied before the product was acceptable.

The removal rate of the polishing process is determined by experiments in which small areas are polished, and the depth of ablation is measured by interferometry. it is advisable for this removal rate to be validated by its successful use in the process of roughness-reduction, according to the method disclosed here.

Roughness reduction is achieved by polishing the surface with a set of short dwell times, corresponding to small removals. The dwell times are chosen such that each

WO 00/32353

PCT/GB99/04014

60

of a set of precession positions (usually four at 90 degrees) removes a depth of material which is less than or equal to four times the current value of Ra, the preferred value being one to two times Ra. As this removal takes place, existing rough features on the polished surface are ablated as new ones are formed.

By removing a depth of one to two times Ra, the new rough feature are much less significant than the previous features. This is illustrated in Figures 32 and 33. Figure 32 shows a rough surface profile, indicating a schematic value of Ra, and indicating that the initial effect of further ablation is to remove peaks. Figure 33 shows the Ra value of roughness on a surface and how it changes with continued ablation. In Figure 33, the line falling to the right indicates the removal of pre-existing roughness features: the line rising to the right indicates the formation of new roughness features. The new roughness feature rise very slowly at first, as the initial ablation merely removes pre-existing peaks, rather than creating new features. As the new and old roughness features have a random character, the sum of old-plus-new feature is the root sum of squares. This is indicated by the dotted curve. An optimum removal occurs at the minimum of the curve indicated by A in Figure 33.

008301 1622860

WO 00/32353

PCT/GB99/04014

61

In practice it is advisable to operate the process cautiously, as unexpected features appear in the polished surface, for example, due to accidental agglomerations of polishing particles. Cautious operation consists in attempting to remove one to two times  $R_a$ , preferably the lower figure. However, it can be economic to remove four times  $R_a$  in the initial stages of the process if the micro-roughness is not well determined owing to the presence of small scratches.

The use of the precession method in these processes causes striations caused by continual rubbing in one direction to cross those in previous passes rather than simply being deepened. After using a set of passes with rubbing directions at 90-degree intervals, it is a refinement in the next step of passes to use the four intermediate rubbing directions at 45 degrees to the first set.

Although the present invention has been described hereinabove with reference to a specific embodiment which uses a soft tool in the form of a bulbous compliant member which is precessed at an angle to the normal of the workpiece, an aspect of the present invention is not limited to this and any form of tool can be used which generates relative lateral movement between the abrading

WO 00/32353

PCT/GB99/04014

62

surface and the workpiece in a direction which can be rotated on the workpiece.

Figure 34 illustrates an alternative working member for use in the head 7 to grind material from the workpiece. This can be used when mass removal of material is required to form the workpiece surface shape before polishing can begin. This working member is not compliant.

As illustrated in Figure 34, the working member is arranged to fit over the tool head 38 of the embodiment of Figure 4. The tool housing 68 is modified slightly at its upper region to include an outer threaded portion to receive an outer housing 200 of a grinding tool. The outer housing 200 is cylindrical and is mounted to the tool housing 68 at an upper end thereof. At a lower end thereof the housing 200 is provided with a plate 201. The plate 201 is clamped to the housing 200 via screws 202 and clamps therebetween a spoked flexible member 203 of similar shape to the spoked member 58 illustrated in Figure 6. The spoked flexible member 203 is clamped at an outer annulus between the plate 201 of the housing 200.

Within the housing 200 there is provided a piston member 204 which is capable of relative vertical movement within the outer housing 200. The piston member 204 has

WO 00/32353

PCT/GB99/04014

63

an upper cylindrical portion which extends around a bush 205 to provide guidance for the vertical movement. The bush 205 rides on an outer surface of the tool housing 68. A lower end of the piston member 204 has a concave surface to receive the membrane 69. In this way the membrane 69 can act on the piston member 204 to drive the piston member 204 axially up and down. The piston member 204 is supported by an inner annulus of the spoked flexible member 203. The inner annulus of the spoked flexible member 203 is provided around a spigot 206 of the piston member 204 and clamped onto the piston member 204 by a nut 207 threaded on the spigot 206. The spigot 206 is arranged to extend through the plate 201. A dome shape grinding member 208 is arranged to be carried on the spigot 206 and locked in place thereby by a nut 209 and washer 210. Thus in this way the dome shape grinding member 208 can be driven up and down by the piston member 204.

Thus this embodiment to the present invention provides a dome shape grinding member 208 which is not compliant but which can be held on the head 7 at an inclined angle and precessed about a precession axis vertical to the workpiece surface being ground. The action of the membrane 69 and the piston member 204 act to provide pressure control on the dome shape grinding



WO 00/32353

PCT/GB99/04014

64

member 208 to thereby allow the control of pressure applied during the grinding action.

Although the embodiments have been described with  
5       bulbous compliant tools, for a convex surface of a  
workpiece a flat or concave compliant tool could be used  
and is within the scope of the present invention.

The embodiment is described as having a fully  
hydraulic pressure applying system. However, the present  
10       invention also encompasses a fluid filled tool head with  
a mechanical pressure transmitting coupling in the tool  
body.

Features of the aspects of the present invention can  
be used in any combination.

15       Since the present invention includes the computer  
control of a polishing machine, the present invention can  
be embodied as a computer program for controlling the  
machine. Thus the present invention includes a carrier  
medium which includes storage media such as floppy disks,  
20       CD ROMS, programmable read only memory devices and  
magnetic tapes, and electrical signals carrying the  
computer program, over a network such as the Internet.

Although the present invention has been described  
hereinabove with reference to specific embodiments, it  
25       will be apparent to a skilled person in the art that the  
present invention is not limited to the specific

T03230" T62/5860

WO 00/32353

PCT/GB99/04014

65

embodiments and modifications can be made within the  
spirit and scope of the invention.

T08280 T6229850

WO 00/32353

PCT/GB99/04014

66

## CLAIMS:

1. A machine for abrading or polishing a workpiece, the machine comprising:

5 a holding surface for holding said workpiece;

a head member arranged along a rotation axis to rotate about the rotation axis;

10 a working member having a surface for abrading or polishing said workpiece arranged on said head member on said rotation axis for rotation about said rotation axis with said head member;

first driving means for driving said head member and said working member mounted thereon to rotate about said rotation axis;

15 head mounting means for mounting said head member;

second driving means for driving said head mounting means to incline said rotation axis of said head member relative to a precession axis intersecting said rotation axis, and for moving said head member to inclined positions with said rotation axis precessed about said precession axis; and

20

third driving means for relatively moving said head mounting means across said holding surface.

25 2. A machine according to claim 1 wherein said first

00857261.032301

WO 00/32353

PCT/GB99/04014

67

driving means is arranged to drive surface of said working member in a lateral direction relative to said holding surface, and said second driving means is adapted to rotate said surface of said working member relative to a position on said holding surface so that a direction of lateral relative movement of said surface of said working member and said holding surface rotate relative to said position on said holding surface.

3. A machine according to claim 1 or claim 2, wherein said second driving means is arranged to move said head member to inclined positions distributed through an integer number of  $360^\circ$  of precession of said rotation axis about said precession axis.

4. A machine according to any preceding claims, wherein said second driving means is arranged to move said head member in precession steps.

5. A machine according to claim 4, wherein said second driving means is arranged to move said head member in precession steps which are symmetrically distributed about the precession axis through an integer number of  $360^\circ$  of angle of precession about the precession axis.

25

0057291.083001

WO 00/32353

PCT/GB99/04014

68

6. A machine according to any one of claims 1 to 4, wherein said second driving means is arranged to incrementally carry out the precession at precession steps which are not an integer division of 360°.

5

7. A machine according to any preceding claim wherein said head mounting means is arranged such that said precession axis intersects said rotation axis at or near said abrasive member.

10

8. A machine according to any preceding claims, including control means for controlling said first and second driving means such that the rate of movement of said head member about said rotation axis is substantially smaller than the rate of rotation of said head member.

15

9. A machine according to any preceding claim, wherein said head mounting means includes first and second arcuate members arranged orthogonally, each with a centre of curvature arranged to lie on an axis passing through or near said working member, said head member being mounted at a second end thereof to said first and second arcuate members by said second driving means to move said

20

T08230" 16225860

WO 00/32353

PCT/GB99/04014

69

second end of said head member in a respective orthogonal arc about a respective axis of the arcuate members.

10. A machine according to any preceding claim, wherein  
5 said third driving means is arranged to also relatively move said head member to and away from said holding surface.

11. A machine according to any preceding claim, wherein  
10 said holding surface is arranged to be relatively rotated with respect to said head mounting means.

12. A machine according to any preceding claim, wherein  
15 said working member is bulbous.

13. A machine according to claim 12, wherein said  
working member is compliant.

14. A machine according to any preceding claim,  
20 including control means operative to receive information on the topography of said workpiece and to control said second driving means to precess said head member about said precession axis normal to the surface of said workpiece at a position being abraded or polished.

25

T03230" T62/5860

WO 00/32353

PCT/GB99/04014

70

15. A machine according to claim 14, wherein said control means is operative to receive information on the roughness of said workpiece and a rate of removal for material removed from said workpiece by said working member, to control said third driving means to move said head mounting means in a repeated figuring pattern and to control said first, second and third driving means to remove less than four times a local roughness average for a region of the workpiece being polished or abraded during each configuring pattern.

16. A machine according to claim 15, wherein said control means is adapted to control said second driving means to use varied inclined positions about said precession axis for each figuring pattern.

17. A method of abrading or polishing the surface of a workpiece, the method comprising:

mounting the workpiece on a holder;  
relatively inclining a head member arranged along a rotation axis and having a working member arranged axially on said rotation axis and on said head member with a surface for abrading or polishing the surface of said workpiece, so that said rotation axis is inclined relative to a precession axis intersecting said rotation

T02200 T624560

WO 00/32353

PCT/GB99/04014

71

axis, said precession axis being normal to the surface of said workpiece at an area of contact of said surface of said working member;

rotation said head member about said rotation axis;

5       contacting said surface of said working member to said surface of said workpiece so that said surface of said working member moves in a direction laterally across said surface of said workpiece;

10       moving the inclined head member to inclined positions rotated about said precession axis; and

moving the incline head member to relatively move said working member and said surface of said workpiece in a figuring pattern.

15       18. A method according to claim 17, wherein the step of moving the inclined head member to inclined positions rotated about said precession axis maintains an angle at which said head member is inclined relative to said precession axis substantially constant.

20

19. A method according to claim 17 or claim 18, wherein said inclined head member is moved in said figuring pattern for each of a plurality of inclined positions rotated about said precession axis.

25

0957291 08304  
108280 1522860



WO 00/32353

PCT/GB99/04014

72

20. A method according to any one of claims 17 to 19, wherein said inclined positions rotated about said precession axis are distributed through an integer number of rotations around said precession axis.

5

21. A method according to any preceding claim, wherein said head member is moved in steps to said inclined positions rotated about said precession axis.

10

22. A method according to claim 21, wherein said inclined positions are symmetrically distributed about said precession axis around an integer number of rotations about said precession axis.

15

23. A method according to claim 21, wherein said inclined positions are not an integer division of 360° of rotation about said precession axis.

20

24. A method according to any one of claims 17 to 23, wherein said precession axis intersects said rotation axis at or near said working member.

25. A method according to any one of claims 17 to 24, wherein the rate of movement of said head member about

09052291 08280 1522560

WO 00/32353

PCT/GB99/04014

73

said precession axis is substantially smaller than the rate of rotation of said head member.

26. A method according to any one of claims 17 to 25, wherein said workpiece is relatively rotated with respect to said head member.

27. A method according to any one of claims 17 to 26, wherein said working member is bulbous.

28. A method according to claim 27, wherein said working member is compliant and the position of said working member relative to said surface of said workpiece is controlled to control the area of contact between said surface of said workpiece and said working member.

29. A method according to any one of claims 17 to 28, wherein the movement of said head member is controlled in dependence upon information on the topology of said workpiece.

30. A method according to claim 29, including receiving information on the roughness of said workpiece and a rate of removal for material removed from said workpiece by said working member, controlling the movement of said

WO 00/32353

PCT/GB99/04014

74

head member to move in a repeated figuring pattern, and controlling the removal of material to remove less than four times a local roughness average for a region of the workpiece being polished or abraded during each figuring pattern.

5

31. A method according to claim 30, wherein varied precession rotations of said head member are used for each figuring pattern.

10

32. A machine for abrading and/or polishing a workpiece, the machine comprising:

15

a holding surface for holding said workpiece;

a head carrying a face for abrading and/or polishing

said workpiece;

a mechanical arrangement for supporting and moving said head across, to and from said holding surface;

20

a tilting mechanism mounted on said mechanical arrangement and arranged to tilt said head about a pivot to an angle relative to said holding surface; and

control means for controlling the position and tilt of said face of said head by controlling said mechanical arrangement and said tilting mechanism, said control means being operative to compensate for the movement of

09857291.082801  
T08280.16225860

WO 00/32353

PCT/GB99/04014

75

said face when tilted by controlling said mechanical arrangement.

33. A machine according to claim 32, wherein said  
5 control means is operative to perform the compensating control by calculating the change in position of said face caused by the tilt.

34. A machine according to claim 32, wherein said  
10 control means is operative to perform the compensating control by looking-up the change in position of said face caused by the tilt.

35. A method of abrading or polishing a workpiece, the  
15 method comprising:

mounting the workpiece on a holder;

moving a head using a mechanical arrangement having  
a face for abrading or polishing said workpiece in a  
figuring pattern;

20 during the figuring, tilting said head about a pivot to an angle relative to said workpiece; and

controlling the position of said head in dependence  
upon the degree of tilt of said head so as to compensate  
for movement of said face relative to said workpiece  
25 caused by tilting said head.

T08280 T622560

WO 00/32353

PCT/GB99/04014

76

36. A method according to claim 35, wherein the movement of said face relative to said workpiece caused by tilting said head is calculated and used to control said mechanical arrangement.

5

37. A method according to claim 35, wherein the movement of said face relative to said workpiece caused by tilting said head is looked-up using the angle of tilt and used to control said mechanical arrangement.

10

38. A carrier medium storing instructions for controlling a processor to control a machine according to any one of claims 1 to 16 or 32 to 34.

15

39. A tool for abrading or polishing a workpiece, the tool comprising:

a bulbous compliant member;

a holder holding said compliant member so that the compliant member bulges there out of;

20

a membrane arranged over a surface of said compliant member to provide a working surface for abrading or polishing said workpiece;

said membrane being flexible to follow the compliance of said compliant member; and

T08280" T62/5860

WO 00/32353

PCT/GB99/04014

77

a membrane carrier carrying said membrane and releasably attached to said holder to allow said membrane and said membrane carrier to be removed from said holder.

5 40. A tool according to claim 39, wherein said membrane carrier is mechanically clamped to said holder.

10 41. A tool according to claim 39 or claim 40, wherein said holder comprises a substantially cylindrical member, said compliant member is held at one end of the cylindrical member and said membrane carrier comprises a substantially cylindrical sleeve fitted over said cylindrical member.

15 42. A tool according to claim 41, wherein said cylindrical member has an outer surface which tapers away from said compliant member and to which said cylindrical sleeve is clamped, and said cylindrical sleeve is shaped to deform to the taper of the outer surface of said  
20 cylindrical member.

43. A tool according to any one of claims 39 to 42, including means to allow said membrane and said surface of said compliant member to move relatively laterally.

25

0957291.08304  
T08280.T62/5865

WO 00/32353

PCT/GB99/04014

78

44. A tool according to claim 43, wherein said means comprises a lubricant or an unset adhesive.

5 45. A tool according to any one of claims 39 to 44, wherein said membrane has an abrasive material bonded thereto or impregnated therein.

10 46. A tool according to claim 45, wherein said membrane is formed of a matrix material and a reinforcing material embedded in said matrix material.

15 47. A tool according to claim 45 or claim 46, wherein said abrasive material is bonded to said membrane in discrete areas over said membrane.

48. A tool according to any one of claims 45 to 47, wherein said abrasive material is bonded to said membrane by epoxy or nickel.

20 49. A tool according to any one of claims 45 to 47, wherein said abrasive material is bound together and bonded to said membrane using a binder material containing an erosion promoter material to promote the erosion of the binder material during abrading or  
25 polishing to expose fresh abrasive material.

09257291.000001

WO 00/32353

PCT/GB99/04014

79

50. A tool according to any one of claims 45 to 49, wherein said abrasive material is bound together and bonded to said membrane using a binder material containing a lubricant material.

5

51. A tool according to any one of claims 39 to 50, wherein said compliant member comprises a volume of fluid and a flexible membrane covering at least in part said volume of fluid, and said volume of fluid is contained by said holder and said flexible membrane in combination and said flexible membrane is sealed to said holder.

10

52. A tool according to any one of claims 39 to 44, wherein said membrane comprises an adsorbant material for adsorbing abrasive material applied thereto for abrading or polishing said workpiece.

15

53. A tool according to claim 52, wherein said membrane is formed of a cloth material.

20

54. An abrasive cup for fitment to a tool for abrading or polishing a workpiece, the abrasive cup comprising:  
a sheet of flexible material having a shape for fitment to a corresponding bulbous compliant member of

T03280" T6245860



WO 00/32353

PCT/GB99/04014

80

said tool, said sheet being sufficiently flexible to flex during abrading; and

5 a carrier carrying said sheet around a periphery of said sheet, said carrier having an arrangement for releasably fixing said abrasive cup to said tool.

55. An abrasive cup according to claim 54, wherein said arrangement comprises a mechanical clamping arrangement.

10 56. An abrasive cup according to claim 54 or claim 55, wherein said carrier comprises a sleeve for fitment to said tool, wherein said sheet is mounted at one end of said sleeve.

15 57. An abrasive cup according to claim 56, wherein said sleeve is shaped to be radially deformable at a second end thereof.

20 58. An abrasive cup according to any one of claims 54 to 57, wherein said sheet has an abrasive material bonded thereto or impregnated therein for abrading or polishing said workpiece.

T09280 16225860

WO 00/32353

PCT/GB99/04014

81

59. An abrasive cup according to claim 58, wherein said sheet comprises a matrix material and a reinforcing material embedded in said matrix material.

5 60. An abrasive cup according to claim 58 or claim 59, wherein said abrasive material is bonded to said sheet in discrete areas over said sheet.

10 61. An abrasive cup according to any one of claims 58 to 60, wherein said abrasive material is bonded to said sheet by epoxy or nickel.

15 62. An abrasive cup according to any one of claims 58 to 61, wherein said abrasive material is bound together and bonded to said sheet using a binder material containing an erosion promoter to promote the erosion of the binder material during abrading or polishing to expose fresh abrasive material.

20 63. An abrasive cup according to any one of claims 58 to 62, wherein said abrasive material is bound together and bonded to said sheet using a binder material containing a lubricant material.

09857291.082001

WO 00/32353

PCT/GB99/04014

82

64. An abrasive cup according to any one of claims 54 to 57, wherein said sheet comprises an adsorbant material for adsorbing abrasive material applied thereto for abrading or polishing said workpiece.

5

65. An abrasive cup according to claim 64, wherein said sheet is formed of a cloth material.

10

66. A method of forming an abrasive cup according to any one of claims 54 to 65, the method comprising:

forming said sheet of material over a carrier into a bulbous shape for fitment to a bulbous compliant member of said tool; and

15

fixing said sheet to said carrier at a periphery of said sheet.

20

67. The method of claim 66, wherein said forming step comprises applying said sheet to a forming tool, and forming said sheet to said bulbous shape.

68. The method of claim 67, including a final step of pressing and/or heating said sheet.

25

69. The method of any one of claims 66 to 68, wherein said sheet comprises a substrate material and the method

T08280 T627860

WO 00/32353

PCT/GB99/04014

83

includes applying a flexible sheet on said substrate material for abrading or polishing said workpiece.

70. A machine for abrading or polishing a workpiece, the machine comprising:

a body extending along a rotation axis and having pressure transmission means at one end of said body, said body being rotatable about said rotation axis;

a head releasably mounted on said end of said body, said head comprising a head housing, a head fluid pressure transmission means, and a resilient membrane forming a sealed head fluid chamber filled with fluid, said head fluid pressure transmission means being arranged in said head housing to cooperate with said pressure transmission means to transmit pressure to said head fluid chamber, and said resilient membrane being held at a periphery thereof by said head housing to extend bulbously therefrom for the application of pressure to said workpiece during abrading or polishing.

20

71. A machine according to claim 70, wherein said body has a body fluid chamber filled with fluid terminating at said pressure transmission means.

09357291.082801  
"T632880"

WO 00/32353

PCT/GB99/04014

84

72. A machine according to claim 71, wherein said body fluid pressure transmission means and said head fluid pressure transmission means comprise respective displacement devices mounted respectively in said body and said head and coupled to one another when said head is mounted to said body.

73. A machine according to claim 71 or claim 72, wherein said body fluid chamber and said head fluid chamber are filled with incompressible fluid.

74. A machine according to any one of claims 71 to 73, including fluid pressure control means comprising a passage from said body fluid chamber, to a fluid pressure control arrangement provided separate to said rotatable body.

75. A machine according to any one of claims 70 to 74, wherein said head is axially mountable to said body.

76. A tool head for releasably mounting on a tool body of a machine for abrading or polishing a workpiece, the tool body having pressure transmission means, the tool head comprising:

WO 00/32353

PCT/GB99/04014

85

a head housing, a head fluid pressure transmission means and a resilient membrane forming a sealed head fluid chamber for holding fluid, said head fluid pressure transmission means being arranged in said head housing to allow the coupling of fluid pressure in said head fluid chamber to said pressure transmission means, and said resilient membrane being held at a periphery thereof by said head housing to extend bulbously therefrom for the application of pressure to said workpiece during abrading or polishing.

77. A tool head according to claim 76, wherein said head fluid transmission means comprises a displacement device for coupling with said pressure transmission means comprising a displacement device when said tool head is mounted on said tool body.

78. A tool head according to claim 76 or claim 77, wherein said head fluid chamber is filled with incompressible fluid.

79. A method of controlling polishing or abrading of a workpiece, the method comprising:

receiving data defining an influence function of a tool, the influence function defining the pattern of

WO 00/32353

PCT/GB99/04014

86

removal of material from the workpiece for a predetermined dwell time or speed of said tool;

receiving data on a desired profile and a current profile of a surface of said workpiece;

5 determining the difference between the desired profile and the current profile to determine a target removal profile;

10 determining dwell times or tool speeds for predetermined positions on said surface of said workpiece to provide a predicted removal profile by performing a numerical optimisation of the dwell times or tool speeds for the predetermined positions using the influence function to reduce at least one cost function; and

15 controlling the polishing or abrading of said workpiece using the determined dwell times.

20 80. A method according to claim 79, wherein said numerical optimisation comprises determining a set of dwell times or tool speeds for the predetermined positions which have a minimum value for a difference between said target removal profile and said predicted removal profile.

25 81. A method according to claim 79, wherein said numerical optimisation comprises a genetic algorithm,

T.03230 T.6275860

WO 00/32353

PCT/GB99/04014

87

wherein values for the dwell times or tool speeds comprise a gene pool for the algorithm.

82. A method according to any one of claims 79 to 81,  
5 wherein said desired profile comprises a desired radial profile for a circular workpiece, said influence function is defined as a 2D function, and the predetermined positions comprise radial positions across said surface of said workpiece.

10

83. A method according to any one of claims 79 to 81,  
wherein said desired profile comprises a desired 3D profile, said influence function is defined as a 3D function, and the determined positions comprise a 2D  
15 array of positions across said surface of said workpiece.

84. A method according to any one of claims 79 to 83,  
wherein a said cost function for predetermined dwell times or tool speed is the sum of squares of the errors  
20 between the target removal profile and the predicted removal profile obtained using the predetermined dwell times.

85. A method according to any one of claims 79 to 84,  
25 wherein said numerical optimisation iteratively searches

T02280 T62/5860



WO 00/32353

PCT/GB99/04014

88

for the best dwell times or tool speeds for said predetermined positions to substantially achieve the desired profile.

- 5 86. A method according to any one of claims 79 to 85, including measuring a profile of said workpiece after polishing, comparing the measured profile with said current profile before polishing to determine a measured removal profile, determining dwell times or tool speeds  
10 expected to achieve said measured removal profile using said numerical optimisation, determining at least one correction factor for dwell times or tool speeds using the dwell times or tool speeds used to polish said workpiece and the dwell times or tool speeds expected to  
15 achieve said measured removal profile, and applying said at least one correction factor to dwell times or tool speeds used in future polishing of said workpiece.

- 20 87. Apparatus for abrading or polishing a workpiece, the apparatus comprising:

first inputting means for inputting data defining an influence function of a tool, the influence function defining the pattern of removal of material from the workpiece for a predetermined dwell time or speed of said  
25 tool;

T08280" T6275860

WO 00/32353

PCT/GB99/04014

89

second inputting means for inputting data on a desired profile and a current profile of a surface of said workpiece;

5 first determining means for determining a target removal profile from the difference between the desired profile and the current profile;

10 second determining means for determining dwell times or tool speeds for predetermined positions on said surface of said workpiece to provide a predicted removal profile by performing a numerical optimisation of the dwell times or tool speeds for the predetermined positions using the influence function to reduce at least one cost function; and

15 control means for controlling the polishing or abrading of said workpiece using said tool and the determined dwell times or tool speeds.

20 88. Apparatus according to claim 87, wherein said second determining means is adapted to determine a set of dwell times or tool speeds which have a minimum value for a difference between said target removal profile and said predicted removal profile.

25 89. Apparatus according to claim 87, wherein said second determining means is adapted to carry out a genetic

09857291.08201  
T08280 "T5275860

WO 00/32353

PCT/GB99/04014

90

algorithm, wherein values for the dwell times or tool speeds for the predetermined positions comprise a gene pool for the algorithm.

5 90. Apparatus according to any one of claims 87 to 89, wherein said second inputting means is adapted to input said desired profile as a desired radial profile for a circular workpiece, said first inputting means is adapted to input said influence function as a 2D function, and  
10 said second determining means is adapted to determine said dwell times or tool speeds for radial positions across said surface of said workpiece.

15 91. Apparatus according to any one of claims 87 to 89, wherein said second inputting means is adapted to input said desired profile as a 3D profile, said first inputting means is adapted to input said influence function as a 3D function, and said second determining means is adapted to determine said dwell times or tool  
20 speeds for a 2D array of positions across said surface of said workpiece.

25 92. Apparatus according to any one of claims 87 to 91, wherein said second determining means is adapted to determine said dwell times or tool speeds using a said

09357291.082801

WO 00/32353

PCT/GB99/04014

91

cost function for determined dwell times or tool speeds comprising the sum of the squares of the errors between the target removal profile and the predicted removal profile obtained using the determined dwell times or tool speeds.

93. Apparatus according to any one of claims 87 to 91, wherein said second determining means is adapted to perform said numerical optimisation iteratively to search for the best dwell times or tool speeds for said predetermined positions to substantially achieve the desired profile.

94. Apparatus according to any one of claims 87 to 93, including measuring means for measuring a profile of said workpiece after polishing, comparing means for comparing the measured profile with said current profile before polishing to determine a measured removal profile, third determining means for determining dwell times or tool speeds expected to achieve said measured removal profile, fourth determining means for determining at least one correction factor for dwell times or tool speeds using the dwell time or tool speeds expected to achieve said measured removal profile and the dwell times or tool speeds used to polish said workpiece, and correction

WO 00/32353

PCT/GB99/04014

92

means for applying said at least one correction factor to dwell times or tool speeds used in future polishing of said workpiece.

5 95. A computer program for controlling a computer to carry out the method of any one of claims 79 to 86.

96. A carrier medium carrying the computer program according to claim 95.

10

97. A method of manufacturing a device comprising the method of any one of claims 17 to 26, 35 to 37 or 79 to 86.


T03280" T62/5860

09/857291

WO 00/32353

PCT/GB99/04014

1 / 27




09/857291

WO 00/32353

2 / 27

PCT/GB99/04014

FIG. 2




09857291.082001

WO 00/32353

3 / 27

09/05/2005  
PCT/GB99/04014








09/857291

WO 00/32353

5 / 27

PCT/GB99/04014

FIG.5




09/057291

WO 00/32353

PCT/GB99/04014

6 1 27

FIG.6



09857291.082801




WO 00/32353

PCT/GB99/04014

8 / 27

FIG. 8




WO 00/32353

09/85729



9 / 27

PCT/GB99/04014

FIG. 9



0957291.08801



09/05729T

WO 00/32353

11 / 27

PCT/GB99/04014

FIG. 12





FIG. 13



095729T.00001



09/07/2001

WO 00/32353

12 / 27

PCT/GB99/04014

FIG. 14a




DEPTH OF "CUT"  
( $\mu\text{m}/\text{sec}$ )

FIG. 14b

FIG. 14c



09/857291

WO 00/32353

13 / 27

PCT/GB99/04014




FIG. 15




FIG. 16




FIG. 17




FIG. 18


09/857291-0001

WO 00/32353

PCT/GB99/04014


14 / 27

FIG. 19



y AXIS


FIG. 20



09/057231

15/27

FIG. 21




09057231-082801

09/857291

WO 00/32353

16 / 27

PCT/GB99/04014



T08280" T62/5860




WO 00/32353

18 / 27

PCT/GB99/04014

FIG. 24




T08280.T6225860

09/85729T

**PCT/GB99/04014**

WO 00/32353

19 / 27






WO 00/32353

20 / 27

PCT/GB99/04014




T08280" T6225860

09/857291

WO 00/32353

21 / 27

PCT/GB99/04014




T08280" T6245860

WO 00/32353

22 / 27

PCT/GB99/04014



09/857291

WO 00/32353

23 / 27

PCT/GB99/04014




FIG. 29


09/857291

WO 00/32353

24 / 27

PCT/GB99/04014

FIG. 30



09857291-082801

09/857291

WO 00/32353

PCT/GB99/04014

25 / 27

FIG. 31a





FIG. 31b



09/857291

WO 00/32353

26 / 27

PCT/GB99/04014

FIG. 32





FIG. 33







## DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that: My residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**A POLISHING MACHINE AND METHOD**

the specification of which:

is attached hereto; or

was filed as United States Application Serial No. 09/857291  
on June 1, 2001, and was amended on June 1, 2001  
(if applicable); or

was filed as PCT International Application Number PCT/GB99/04014  
on December 1, 1999 and was amended on \_\_\_\_\_  
(if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate or § 365(a) of any PCT international application(s), designating at least one country other than the United States, listed below and have also identified below any foreign application(s) for patent or inventor's certificate, or any PCT international application(s) having a filing date before that of the application(s) of which priority is claimed:

| Country        | Application Number | Date of Filing   | Priority Claimed Under 35 U.S.C. 119                                |
|----------------|--------------------|------------------|---|
| United Kingdom | 9826369.2          | December 1, 1998 | <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO |
| United Kingdom | 9826371.8          | December 1, 1998 | <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO |
| United Kingdom | 9826372.6          | December 1, 1998 | <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO |

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below:

| Application Number | Date of Filing |
|--------------------|----------------|
|                    |                |
|                    |                |

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) or § 365(c) of any PCT international application(s) designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application(s) in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

09857291-16225860

| Application Number | Date of Filing | Status (Patented, Pending, Abandoned) |
|--------------------|----------------|---------------------------------------|
|                    |                |                                       |

70

I hereby appoint the following attorney and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. **FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P.**, Reg. No. 22,540; Douglas B. Henderson, Reg. No. 20,291; Ford F. Farabow, Jr., Reg. No. 20,630; Arthur S. Garrett, Reg. No. 20,338; Donald R. Dunner, Reg. No. 19,073; Brian G. Brunsvold, Reg. No. 22,593; Tipton D. Jennings IV, Reg. No. 20,645; Jerry D. Voight, Reg. No. 23,020; Laurence R. Hefter, Reg. No. 20,827; Kenneth E. Payne, Reg. No. 23,098; Herbert H. Mintz, Reg. No. 26,691; C. Larry O'Rourke, Reg. No. 26,014; Albert J. Santorelli, Reg. No. 22,610; Michael C. Elmer, Reg. No. 25,857; Richard H. Smith, Reg. No. 20,609; Stephen L. Peterson, Reg. No. 26,325; John M. Romary, Reg. No. 26,331; Bruce C. Zotter, Reg. No. 27,680; Dennis P. O'Reilly, Reg. No. 27,932; Allen M. Sokal, Reg. No. 26,695; Robert D. Bajefsky, Reg. No. 25,387; Richard L. Stroup, Reg. No. 28,478; David W. Hill, Reg. No. 28,220; Thomas L. Irving, Reg. No. 28,619; Charles E. Lipsey, Reg. No. 28,165; Thomas W. Winland, Reg. No. 27,605; Basil J. Lewris, Reg. No. 28,818; Martin I. Fuchs, Reg. No. 28,508; E. Robert Yoches, Reg. No. 30,120; Barry W. Graham, Reg. No. 29,924; Susan Haberman Griffen, Reg. No. 30,907; Richard B. Racine, Reg. No. 30,415; Thomas H. Jenkins, Reg. No. 30,857; Robert E. Converse, Jr., Reg. No. 27,432; Clair X. Mullen, Jr., Reg. No. 20,348; Christopher P. Foley, Reg. No. 31,354; John C. Paul, Reg. No. 30,413; David M. Kelly, Reg. No. 30,953; Kenneth J. Meyers, Reg. No. 25,146; Carol P. Einaudi, Reg. No. 32,220; Walter Y. Boyd, Jr., Reg. No. 31,738; Steven M. Anzalone, Reg. No. 32,095; Jean B. Fordis, Reg. No. 32,984; Barbara C. McCurdy, Reg. No. 32,120; James K. Hammond, Reg. No. 31,964; Richard V. Burgujian, Reg. No. 31,744; J. Michael Jakes, Reg. No. 32,824; Dirk D. Thomas, Reg. No. 32,600; Thomas W. Banks, Reg. No. 32,719; Christopher P. Isaac, Reg. No. 32,616; Bryan C. Diner, Reg. No. 32,409; M. Paul Barker, Reg. No. 32,013; Andrew Chanho Sonu, Reg. No. 33,457; David S. Forman, Reg. No. 33,694; Vincent P. Kovalick, Reg. No. 32,867; James W. Edmondson, Reg. No. 33,871; Michael R. McGurk, Reg. No. 32,045; Joann M. Neth, Reg. No. 36,363; Gerson S. Panitch, Reg. No. 33,751; Cheri M. Taylor, Reg. No. 33,216; Charles E. Van Horn, Reg. No. 40,266; and Linda A. Wadler, Reg. No. 33,218; Jeffrey A. Berkowitz, Reg. No. 36,743; Michael R. Kelly, Reg. No. 33,921; James B. Monroe, Reg. No. 33,971; Doris Johnson Hines, Reg. No. 34,629; Allen R. Jensen, Reg. No. 28,224; Lori Ann Johnson, Reg. No. 34,498; and David A. Manspeizer, Reg. No. 37,540 and \_\_\_\_\_ . Please address all correspondence to **FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P.**, 1300 I Street, N.W., Washington, D.C. 20005, Telephone No. (202) 408-4000.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

1-00

|  |  |   |
|--|--|---|
| <b>Full Name of first Inventor</b><br>Richard Bingham  | <b>Inventor's Signature</b><br><i>RG Bingham</i> | <b>Date</b><br>17 July 2001                     |
| <b>Residence</b><br>Cambridge, United Kingdom GBX  |  | <b>Country of Citizenship</b><br>United Kingdom |
| <b>Post Office Address</b><br>MILLINGTON<br>29 Lymington Road, Cambridge CB3 9HW, United Kingdom |  |   |

2-00

|  |   |   |
|--|---|---|
| <b>Full Name of Second Inventor</b><br>David Charles Riley   | <b>Inventor's Signature</b><br><i>David C Riley</i> | <b>Date</b><br>8-7-1                            |
| <b>Residence</b><br>Nottingham, United Kingdom GBX   |   | <b>Country of Citizenship</b><br>United Kingdom |
| <b>Post Office Address</b><br>6 Thomas Avenue, Radcliffe on Trent, Nottingham NG12 2HT, United Kingdom |   |   |